Earthing & Lightning | EARTH RODS & ACCESSORIES

EARTH RODS and ACCESSORIES



Wiring Terminals

Jointing

Heatshrink

Junction Boxes

Fixing & Security




'U' Bolt Double Plate Clamp

'U' Bolt Double Plate Clamps are designed to join 25 x 3 conductor tape to the earth electrode / rebar, without the need to drill the tape. The clamps have a high resistance to corrosion and are mechanically strong to ensure a lasting connection.

Body Material: High strength copper alloy

19 / ¾"

'U' Bolt Material: Copper **Standards:** BS 7430





37.0

25.0





'B' Bond

FRUB19B

B' type Bond connections are designed to bond either copper or aluminium conductor to flat metal surfaces

Material: Gunmetal Standards: BS 7430





Code	Maximum Tape Width	Bolt Size	Conductor Material
BN105	26	M10	Copper





RWP Bond Clamp

RWP type Bond connections are designed to connect flat conductor to circular objects ie pipework and hand rails etc.

Material: Gunmetal Standards: BS 7430





Code	Maximum Tape Width	Bolt Size	Conductor Material
BN115	26	M10	Copper



EC1 Earthing Clamp

EC1 earth clamp for large diameter circular objects ie. pipework and hand rails etc.

Strap Material: Stainless Steel (304 grade)
Body Material: Phosphorus Bronze

Label Material: Aluminium



Terminal Size	Strap Length	Pipe Diameter
2.5 - 10.0mm ²	1,600.0	50.0 to 450.0