


# Accessories | HAZARDOUS AREA CONVERTERS

## HAZARDOUS AREA NPT-METRIC



### NPT-Metric Hazardous Adaptors

Enlarges housing entry thread.

- NPT - ISO Metric range.
- Application; Hazardous Area, Machines, Devices, Housings, Panels

**Standards:** IECEx: Ex d I/IIC Mb/Gb, Ex e I/IIC Mb/Gb, Ex t IIIC Db

ATEX: Ex d IIC Gb, Ex e IIC Gb, Ex tb IIIC Db, II 2 GD


**Protection:** IP66 / IP67 / IP68 (2m cont.)

**Temperature Range:** -20°C to 95°C

**Material:** Brass or Nickel Plated Brass



Code	Entry Thread		Thread Length		A/F	A/C	Hex Length Min (G)
	Male	Female	Male (L1)	Female (F)			
AN050M20E-UN	½" / 0.50 NPT	M20 x 1.5	15.0	15.0	27.0	30.4	21.0
AN075M25E-UN	¾" / 0.75 NPT	M25 x 1.5	15.0	15.0	32.0	36.0	21.0



### NPT-Metric Hazardous Reducers

Reduces housing entry thread.

- NPT - ISO Metric range.
- Application; Hazardous Area, Machines, Devices, Housings, Panels

**Standards:** IECEx: Ex d I/IIC Mb/Gb, Ex e I/IIC Mb/Gb, Ex t IIIC Db

ATEX: Ex d IIC Gb, Ex e IIC Gb, Ex tb IIIC Db, II 2 GD

**Protection:** IP66 / IP67 / IP68 (2m cont.)

**Temperature Range:** -20°C to 95°C

**Material:** Brass or Nickel Plated Brass



Code	Entry Thread		Thread Length		A/F	A/C	Hex Length Min (G)
	Male	Female	Male (L1)	Female (F)			
RN075M20E-UN	¾" / 0.75 NPT	M20 x 1.5	15.0	15.0	27.0	30.4	6.0
RN100M20E-UN	1" / 1.00 NPT	M20 x 1.5	15.0	19.0	35.0	39.4	6.0
RN100M25E-UN	1" / 1.00 NPT	M25 x 1.5	15.0	19.0	42.0	47.3	6.0
RN125M20E-UN	1¼" / 1.25 NPT	M20 x 1.5	15.0	19.0	42.0	47.3	6.0
RN125M25E-UN	1¼" / 1.25 NPT	M25 x 1.5	15.0	19.0	42.0	47.3	6.0
RN125M32E-UN	1¼" / 1.25 NPT	M32 x 1.5	15.0	19.0	42.0	47.3	6.0
RN150M20E-UN	1½" / 1.50 NPT	M20 x 1.5	15.0	21.0	48.0	54.0	6.0
RN150M25E-UN	1½" / 1.50 NPT	M25 x 1.5	15.0	21.0	48.0	54.0	6.0
RN150M32E-UN	1½" / 1.50 NPT	M32 x 1.5	15.0	21.0	48.0	54.0	6.0
RN150M40E-UN	1½" / 1.50 NPT	M40 x 1.5	15.0	21.0	48.0	54.0	6.0