



LOCKNUTS



Stainless Steel Locknuts

Stainless Steel Locknuts are recommended for use where prolonged submersion or increased corrosion resistance is required. Manufactured from 316 (A4) Stainless Steel.

Temperature Range: -100°C to 400°C

Material: 316 (A4) Stainless Steel



Stainless

Code	Entry Thread	A/F	A/C	Thickness
SSLN12	M12 x 1.5	15.0	16.5	3.0
SSLN16	M16 x 1.5	22.0	24.0	4.0
SSLN1	M20 x 1.5	25.4	27.9	4.0
SSLN2	M25 x 1.5	30.0	33.0	4.0
SSLN3	M32 x 1.5	40.0	44.0	4.0
SSLN4	M40 x 1.5	46.0	50.5	4.8
SSLN5	M50 x 1.5	65.0	71.5	5.0
SSLN6	M63 x 1.5	80.0	88.0	6.4
SSLN7	M75 x 1.5	90.0	99.0	7.0
SSLN8	M80 x 2.0	90.0	99.0	9.0
SSLN9	M90 x 2.0	104.8	115.3	9.0
SSLN10	M100 x 2.0	114.3	125.7	9.0

Code	Entry Thread	A/F	A/C	Thickness
SSLN050NPT	½" NPT	27.0	29.7	3.2
SSLN075NPT	¾" NPT	30.5	33.5	4.0
SSLN100NPT	1" NPT	36.0	39.5	6.4
SSLN125NPT	1¼" NPT	46.0	50.5	6.4
SSLN150NPT	1½" NPT	55.0	60.6	6.4
SSLN200NPT	2" NPT	65.0	70.8	6.4
SSLN250NPT	2½" NPT	90.0	99.0	9.0
SSLN300NPT	3" NPT	104.8	115.3	9.0
SSLN350NPT	3½" NPT	114.3	125.7	10.0

Aluminium Locknuts

Aluminium Locknuts are recommended when installing aluminium Cable Glands to prevent the galvanic corrosion which can occur when dissimilar metals are coupled together.

Temperature Range: -60°C to 130°C

Material: Aluminium 6082 HE30



Aluminium

Code	Entry Thread	A/F	A/C	Thickness
ALN16	M16 x 1.5	24.0	36.4	4.0
ALN1	M20 x 1.5	27.0	29.7	4.0
ALN2	M25 x 1.5	30.0	33.0	4.0
ALN3	M32 x 1.5	40.0	44.0	4.0
ALN4	M40 x 1.5	50.0	55.0	4.5
ALN5	M50 x 1.5	65.0	71.5	5.0
ALN6	M63 x 1.5	75.0	82.5	6.5
ALN7	M75 x 1.5	90.0	99.0	7.0