


Accessories | HAZARDOUS AREA CONVERTERS

HAZARDOUS AREA METRIC-METRIC



Metric-Metric Hazardous Adaptors & Reducers

Enlarges housing entry thread.

• ISO Metric range.

• Application; Hazardous Area, Machines, Devices, Housings, Panels

Standards: IECEx: Ex d I/IIC Mb/Gb, Ex e I/IIC Mb/Gb, Ex t I/IIC Db

ATEX: Ex d IIC Gb, Ex e IIC Gb, Ex tb IIIC Db, II 2 GD

Protection: IP66 / IP67 / IP68 (2m cont.)

Temperature Range: -20°C to 95°C

Material: Brass or Nickel Plated Brass



Code	Entry Thread		Thread Length				Hex Length
	Male	Female	Male (L1)	Female (F)	A/F	A/C	Min (G)
AM16M20E-UN	M16 x 1.5	M20 x 1.5	15.0	15.0	27.0	30.4	21.0
AM16M25E-UN	M16 x 1.5	M25 x 1.5	15.0	15.0	27.0	30.4	21.0
AM20M25E-UN	M20 x 1.5	M25 x 1.5	15.0	15.0	32.0	36.0	21.0
AM20M32E-UN	M20 x 1.5	M32 x 1.5	15.0	15.0	32.0	36.0	21.0
AM25M32E-UN	M25 x 1.5	M32 x 1.5	15.0	15.0	38.0	42.8	21.0
AM25M40E-UN	M25 x 1.5	M40 x 1.5	15.0	15.0	38.0	42.8	21.0
AM32M40E-UN	M32 x 1.5	M40 x 1.5	15.0	15.0	50.0	56.3	21.0
AM32M50E-UN	M32 x 1.5	M50 x 1.5	15.0	15.0	50.0	56.3	21.0
AM40M50E-UN	M40 x 1.5	M50 x 1.5	15.0	15.0	60.0	67.5	21.0
AM40M63E-UN	M40 x 1.5	M63 x 1.5	15.0	15.0	60.0	67.5	21.0
AM50M63E-UN	M50 x 1.5	M63 x 1.5	15.0	15.0	70.0	78.8	21.0
AM50M75E-UN	M50 x 1.5	M75 x 1.5	15.0	15.0	70.0	78.8	21.0
AM63M75E-UN	M63 x 1.5	M75 x 1.5	15.0	15.0	80.0	90.0	21.0

Code	Entry Thread		Thread Length				Hex Length
	Male	Female	Male (L1)	Female (F)	A/F	A/C	Min (G)
RM20M16E-UN	M20 x 1.5	M16 x 1.5	15.0	15.0	27.0	30.4	6.0
RM25M16E-UN	M25 x 1.5	M16 x 1.5	15.0	15.0	32.0	36.0	6.0
RM25M20E-UN	M25 x 1.5	M20 x 1.5	15.0	15.0	32.0	36.0	6.0
RM32M16E-UN	M32 x 1.5	M16 x 1.5	15.0	15.0	38.0	42.8	6.0
RM32M20E-UN	M32 x 1.5	M20 x 1.5	15.0	15.0	38.0	42.8	6.0
RM32M25E-UN	M32 x 1.5	M25 x 1.5	15.0	15.0	38.0	42.8	6.0
RM40M20E-UN	M40 x 1.5	M20 x 1.5	15.0	15.0	47.0	52.9	6.0
RM40M25E-UN	M40 x 1.5	M25 x 1.5	15.0	15.0	47.0	52.9	6.0
RM40M32E-UN	M40 x 1.5	M32 x 1.5	15.0	15.0	47.0	52.9	6.0
RM50M20E-UN	M50 x 1.5	M20 x 1.5	15.0	15.0	55.0	61.9	6.0
RM50M25E-UN	M50 x 1.5	M25 x 1.5	15.0	15.0	55.0	61.9	6.0
RM50M32E-UN	M50 x 1.5	M32 x 1.5	15.0	15.0	55.0	61.9	6.0
RM50M40E-UN	M50 x 1.5	M40 x 1.5	15.0	15.0	55.0	61.9	6.0
RM63M20E-UN	M63 x 1.5	M20 x 1.5	15.0	15.0	70.0	78.8	6.0
RM63M25E-UN	M63 x 1.5	M25 x 1.5	15.0	15.0	70.0	78.8	6.0
RM63M32E-UN	M63 x 1.5	M32 x 1.5	15.0	15.0	70.0	78.8	6.0
RM63M40E-UN	M63 x 1.5	M40 x 1.5	15.0	15.0	70.0	78.8	6.0
RM63M50E-UN	M63 x 1.5	M50 x 1.5	15.0	15.0	70.0	78.8	6.0
RM75M20E-UN	M75 x 1.5	M20 x 1.5	15.0	15.0	80.0	90.0	6.0
RM75M25E-UN	M75 x 1.5	M25 x 1.5	15.0	15.0	80.0	90.0	6.0
RM75M32E-UN	M75 x 1.5	M32 x 1.5	15.0	15.0	80.0	90.0	6.0
RM75M40E-UN	M75 x 1.5	M40 x 1.5	15.0	15.0	80.0	90.0	6.0
RM75M50E-UN	M75 x 1.5	M50 x 1.5	15.0	15.0	80.0	90.0	6.0
RM75M63E-UN	M75 x 1.5	M63 x 1.5	15.0	15.0	80.0	90.0	6.0