

# NON-METALLIC CONDUIT | Flexible Conduit Systems

## FLEXIBLE CONDUIT ACCESSORIES

### Straight Gland - Polypropylene

• Straight glands are supplied including locknuts

**Temperature Range:** -5°C to 90°C

**Material:** Polypropylene

**IP Rating:** IP44

**Colour:** Black and White



Black		White	
Code	Code	Thread Size	Conduit Size
PVF16	PVF16-W	M16 x 1.5	16
PVF20	PVF20-W	M20 x 1.5	20
PVF25	PVF25-W	M25 x 1.5	25
PVF32	PVF32-W	M32 x 1.5	32
PVF40	PVF40-W	M40 x 1.5	40
PVF50	PVF50-W	M50 x 1.5	50



### U Clamp - Polypropylene

**Material:** PA66 (Nylon)

**Colour:** Black



Code	Colour	Conduit Size
UC12	Black	12
UC16	Black	16
UC20	Black	20
UC25	Black	25
UC32	Black	32
UC40	Black	40
UC50	Black	50



### P Clip Galvanised Steel

**Material:** Galvanised Steel / Elastomer Liner

**Colour:** Black




Code	Colour	Conduit Size
PC12	Black	12
PC16	Black	16
PC20	Black	20
PC25	Black	25
PC32	Black	32
PC40	Black	40
PC50	Black	50



### Conduit Cutting Tools

• Conduit cutting tool, ideal for cutting conduit 10mm to 40mm

**Material:** Steel



Code	Description	Cutting Capacity
CCT42	Conduit cutting tool	6 - 42

