


Accessories | INDUSTRIAL AREA CONVERTERS

METRIC BRASS ADAPTORS AND REDUCERS



Metric-Metric Industrial Adaptors

- ISO Metric range.
- Application; Machines, Devices, Housings, Panels

Standards: EN 50262

Protection: IP54

IP66 (if fitted with sealing washer)

Temperature Range: -60°C to 200°C

Material: Nickel Plated Brass



Code	Entry Thread		Thread Length		A/F	Body Height
	Male	Female	Male (L1)	Female (F)		
AM16M20S	M16 x 1.5	M20 x 1.5	13.0	13.0	24.0	15.0
AM20M25S	M20 x 1.5	M25 x 1.5	13.0	13.0	29.0	15.0
AM25M32S	M25 x 1.5	M32 x 1.5	13.0	13.0	36.0	15.0
AM32M40S	M32 x 1.5	M40 x 1.5	13.0	15.0	44.0	17.5
AM40M50S	M40 x 1.5	M50 x 1.5	13.0	15.0	54.0	17.5
AM50M63S	M50 x 1.5	M63 x 1.5	13.0	15.0	72.0	20.5
AM63M75S	M63 x 1.5	M75 x 1.5	13.0	18.0	79.0	20.5

Metric-Metric Industrial Reducers

- ISO Metric range.
- Application; Machines, Devices, Housings, Panels

Standards: EN 50262

Protection: IP54

IP66 (if fitted with sealing washer)

Temperature Range: -60°C to 200°C

Material: Nickel Plated Brass



Code	Entry Thread		Thread Length		A/F	Body Height
	Male	Female	Male (L1)	Female (F)		
RM16M12S	M16 x 1.5	M12 x 1.5	10.0	18.0	4.0	
RM20M12S	M20 x 1.5	M12 x 1.5	13.0	22.0	4.0	
RM20M16S	M20 x 1.5	M16 x 1.5	13.0	22.0	4.0	
RM25M16S	M25 x 1.5	M16 x 1.5	13.0	27.0	5.5	
RM25M20S	M25 x 1.5	M20 x 1.5	13.0	27.0	5.5	
RM32M20S	M32 x 1.5	M20 x 1.5	13.0	34.0	5.5	
RM32M25S	M32 x 1.5	M25 x 1.5	13.0	34.0	5.5	
RM40M20S	M40 x 1.5	M20 x 1.5	13.0	43.0	5.5	
RM40M25S	M40 x 1.5	M25 x 1.5	13.0	43.0	5.5	
RM40M32S	M40 x 1.5	M32 x 1.5	13.0	43.0	5.5	
RM50M20S	M50 x 1.5	M20 x 1.5	13.0	53.0	5.5	
RM50M25S	M50 x 1.5	M25 x 1.5	13.0	53.0	5.5	
RM50M32S	M50 x 1.5	M32 x 1.5	13.0	53.0	5.5	
RM50M40S	M50 x 1.5	M40 x 1.5	13.0	53.0	5.5	
RM63M20S	M63 x 1.5	M20 x 1.5	13.0	66.0	5.5	
RM63M25S	M63 x 1.5	M25 x 1.5	13.0	66.0	5.5	
RM63M32S	M63 x 1.5	M32 x 1.5	13.0	66.0	5.5	
RM63M40S	M63 x 1.5	M40 x 1.5	13.0	66.0	5.5	
RM63M50S	M63 x 1.5	M50 x 1.5	13.0	66.0	5.5	
RM75M63S	M75 x 1.5	M63 x 1.5	13.0	78.0	5.5	