

Cable Glands | INDUSTRIAL CCG® CABLE GLANDS

INDOOR/OUTDOOR - STEEL WIRE ARMOUR

Cable Glands
Accs.
Wiring Terminals
Tube Lugs
Tooling
Earthing Lightning
Joining
Heat-shrink
Junction Boxes
Cable Crabs
Cable Ties
MICC Cable
Conduit
Fixing & Security



CCG CW Cable Gland

The CW Gland is designed for use with Steel Wire Armoured cables for general indoor/outdoor use where a seal on the outer sheath is required to obtain an IP rating. The gland features two-piece handling, no loose parts & freely rotating captive cone providing an armour clamp and earth bond without twisting the armouring. Seals on the cable sheath to IP66 if fitted with a sealing washer.

- For indoor and outdoor use.
- Two-part handling, no loose parts.
- Freely rotating captive cone, providing an armour clamp and earth bond without twisting the armouring.
- Patented disconnect armour clamp system for ease of inspection.
- Supplied complete with IP sealing washer.

Standards: EN 50262 IEC 62444
SANS/SABS 1213 BS 6121 Part 1
SGS 3641/9369

Installation: MASC 11-303 BS 7430
AS/NZS 3000 BS 6121-5 IEC 60364-5-54
BS 7671 SANS 0142

Marine: ABS 14-SG246753-2-PDA / DNV-GL TAE000000Z



EMC Compatible: SGS EMC197708/1

London Underground Approval: 3043

Protection: IP66 - MASC 11-263

Temperature Range: -20°C to 125°C

Material (Gland): Brass (Nickel Plated) BS 2874 / EN 12164

Material (Seal): Thermoset Elastomer



Reference Bedding OD (A) Cable OD (B) Gland Armour Dia (F) Thread

Code	Kit Code	LS Kit Code	Size	Max	Min	Max	Length (L2)	Min	Max	Entry (C)	Length (L1)	A/F	A/C
051216	GPCW16	GPCW16LS	00 - 16ss	8.5	8.0	13.5	55.0	0.09	0.09	M16 x 1.5	10.0	24.0	27.0
051200	GPCW00	GPCW00LS	00 - 20ss	8.5	8.0	13.5	55.0	0.90	0.90	M20 x 1.5	10.0	24.0	27.0
0512-0	GPCW0	GPCW0LS	0 - 20s	12.0	11.5	16.0	55.0	0.90	1.25	M20 x 1.5	10.0	24.0	27.0
051201	GPCW1	GPCW1LS	1 - 20	15.0	14.5	20.5	60.0	0.90	1.25	M20 x 1.5	10.0	27.0	30.0
051202	GPCW2	GPCW2LS	2 - 25	20.0	20.5	26.5	70.0	1.25	1.60	M25 x 1.5	10.0	35.0	39.0
051203	GPCW3	GPCW3LS	3 - 32	26.5	26.5	33.5	76.0	1.60	2.00	M32 x 1.5	10.0	42.0	47.0
051204	GPCW4	GPCW4LS	4 - 40	34.0	33.0	42.5	90.0	1.60	2.00	M40 x 1.5	15.0	52.0	59.0
051205	GPCW5	GPCW5LS	5 - 50	44.5	42.5	52.5	99.0	2.00	2.50	M50 x 1.5	15.0	65.0	73.0
051206	GPCW6	GPCW6LS	6 - 63	56.5	52.5	65.5	120.0	2.00	2.50	M63 x 1.5	15.0	80.0	90.0
051207	GPCW7	GPCW7LS	7 - 75	67.5	65.5	78.0	143.0	2.50	3.15	M75 x 1.5	15.0	96.0	108.0
051208	GPCW8	GPCW8LS	8 - 80	74.0	78.0	82.0	143.0	2.50	3.15	M80 x 2.0	20.0	96.0	108.0
051209	GPCW9	GPCW9LS	9 - 90	81.5	82.0	91.0	143.0	3.00	3.50	M90 x 2.0	20.0		
051210	GPCW10	GPCW10LS	10 - 100	91.0	90.0	100.0	143.0	3.00	3.50	M100 x 2.0	20.0		

Kits and Accessories

CW Glands can also be supplied in kits complete with;
2 glands, 2 locknuts, 2 earhtags, 2 PVC shrouds (M16-M32)
1 gland, 1 locknut, 1 earhtag, 1 PVC shroud (M40-M100)

