

# HYDRAULIC CRIMPING & CUTTING | Tooling & Cable Prep

## HYDRAULIC CRIMP and CUTTING TOOLING



### Hydraulic Foot Pump

Hydraulic foot pump tool used for connecting with different hydraulic working heads. The tool has a small volume capacity which is light weight and easy to carry.

**Max Output Pressure:** 2.0 Mpa Low Pressure / 70 Mpa High Pressure

**Oil Output:** 11ml Low Pressure / 1.4ml High Pressure

**Oil Capacity:** 700cc

**Weight:** 9.0Kgs



Code	Description	Tool Dimensions (LxWxH)
HFP	Hydraulic Foot Pump	450x150x200



### Hydraulic Hexagon Crimping Head 10.0 to 630.0mm<sup>2</sup>

Hydraulic hexagon crimping head for uninsulated copper tube terminals from 10.0 to 630.0mm<sup>2</sup>.

**Crimping Range:** 10.0 to 630.0mm<sup>2</sup>

**Length:** 290mm

**Weight:** 5.50Kgs



Code	Description	Tool Length	Crimping Capacity (mm <sup>2</sup> )
HCH630	Hydraulic Hexagon Crimping Head	290.0	10.0 - 630.0



### Hydraulic Cutting Head up to 100mm Diameters

Hydraulic cutting head tool for suitable for cables up to 100mm diameters.

**Cutting Range:** up to 100mm diameter

**Cutting Force:** 60KN

**Oil Capacity:** 15ml

**Length:** 515mm

**Weight:** 8.40Kgs



Code	Description	Tool Length	Cutting Capacity (mm OD)
HCH100	Hand Hydraulic Cutting Tool	515.0	up to 100.0



Call the Remora sales team at **01226 352 000**

Challenge us - We find a solution

Cable Glands  
Accs.  
Wiring Terminals  
Tube Lugs  
Tooling  
Earthing/Lighting  
Joining  
Heat-shrink  
Junction Boxes  
Cable Cleats  
Cable Ties  
MCC Cable  
Conduit  
Fixing & Security