

GRIPLOC® METALLIC CABLE GLANDS | Cable Glands

GRIPLOC® STAINLESS STEEL CABLE GLANDS

Stainless Steel GripLoc® Glands Metric

- Standard Metric range of Stainless Steel cable glands.
- GripLoc Seal® - Superior Ingress Protection, mechanical grip and cable retention.


Standards: EN 50262

Protection: IP69K / IP68 10 bar (150 PSI)

Temperature Range: -40°C to 100°C (static) (120° Instantaneous)

Material (Gland): 304 Stainless Steel ¹

Material (Seal): NBR Seal and EPDM O-Ring



Code	Cable Range (B)		Entry Thread Size	Gland		
	Min	Max		Length (L1)	Length (L2)	A/F
GripLoc-SS-M12	2.0	5.0	M12 x 1.5	6.5	25.5	14.0
GripLoc-SS-M16	4.0	8.0	M16 x 1.5	6.0	27.0	19.0
GripLoc-SS-M20	6.0	12.0	M20 x 1.5	6.0	29.0	22.0
GripLoc-SS-M20L	10.0	14.0	M20 x 1.5	6.0	30.0	24.0
GripLoc-SS-M25	13.0	18.0	M25 x 1.5	7.0	32.0	30.0
GripLoc-SS-M32	18.0	25.0	M32 x 1.5	8.0	39.0	40.0
GripLoc-SS-M40	22.0	32.0	M40 x 1.5	8.0	45.0	50.0
GripLoc-SS-M50	32.0	38.0	M50 x 1.5	9.0	46.0	57.0
GripLoc-SS-M63	37.0	44.0	M63 x 1.5	10.0	48.0	68.0

¹ 316 Stainless Steel available to order

Cable Glands
Accs.
Wiring Terminals
Tube Lugs
Tooling
Earthing/Lightning
Joining
Heat-shrink
Junction Boxes
Cable Cleats
Cable Ties
MCC Cable
Conduit
Fixing & Security