



Pre Boxed Heatshrink Dispensers

With excellent electrical and mechanical properties, it is flexible and has a low shrinkage temperature. Applications include general electrical insulation, mechanical protection, cable and harness bundling, sleeving and colour identification. It is widely used in electrical, electronic, automotive, mechanical and general commercial industries. Remora's heat shrink boxed sleeving is available in sizes from 1.5mm to 25.4mm internal diameter and is available in nine different colours. Supplied in lengths from 3m to 15m in convenient point of sale packaging. Remora Heatshrink tube is also available as a in the Mini Kit RMK1.

Temperature Range: -40°C to 135°C

Material: Flame Retardant Self Extinguishing Polyolefin

Colour: Black, Blue, Brown, Clear, Grey, Green, Green/Yellow, Red, Yellow



Code	Internal Diameter		Shrunk Wall Thickness	Supplied Form	Fits Tri-Rated Cable mm ²	Box Reel Length (m)
	Max Before Shrink	Min After Shrink				
HSB3*	3.2	1.6	0.5	Round	0.5 - 0.75	15
HSB4*	4.8	2.4	0.5	Round	0.75 - 2.5	10
HSB6*	6.4	3.2	0.65	Round	2.5 - 6.0	10
HSB9*	9.5	4.7	0.65	Flat 15	6.0 - 10	10
HSB13*	12.7	6.4	0.65	Flat 20	10 - 25	8
HSB20*	19.1	9.5	0.75	Flat 30	35 - 70	5
HSB25*	25.4	12.7	0.9	Flat 40	95 - 120	3

