

FLEXIBLE GALVANISED STEEL CONDUIT

Galvanised Steel

Galvanised Steel - PVC Coated Conduit

Galvanised Steel, helically wound flexible conduit with tough PVC coating. Ideal for general use where mechanical protection is required, commonly used in general factory wiring and connections to machinery. Metallic conduit systems offer higher compression strength than non-metallic. The flexible body facilitates easy installation with cornering and elbow options. Metallic conduit systems have superior protection and protection from electromagnetic interference and good mechanical abrasion resistance. Crush resistance of 1500N.

Cable Glands
Accs.
Wiring Terminals
Tubes
Tooling
Earthing/Lighting
Joining
Heat-shrink
Junction Boxes
Cable Cleats
Cable Ties
MIGC Cable
Conduit
Fixing & Security



Galvanised Steel - CC Range

- High mechanical strength
- Highly flexible
- IP rating: IP40
- Temperature range: -50°C to +300°C
- Nickel plated brass fittings
- Wide Size range 16mm to 100mm
- Low Fire Hazard

Galvanised Steel - FPCC Range

- High mechanical strength
- Highly flexible
- IP rating: IP54
- Temperature range: -20°C to +80°C
- Nickel plated brass fittings
- Wide Size range 16mm to 100mm
- FPCC offers high abrasion resistance

Contractor Packs

- Pack consists of 10 meter of steel conduit and 10 straight fittings including 10 locknuts.

Temperature Range: -50°C to 300°C

Crush Resistance: 1500N

IP Rating: IP40

Material: Galvanised Steel to DIN 53210

Standards: EN 50086



Code	Conduit Size	Conduit ID	Conduit OD	Coil (m)
CON/GALV/20	20	17.0	21.0	10
CON/GALV/25	25	22.0	27.0	10

