# MULTI PURPOSE FIXING BAND | Cable Ties & Banding

MULTI PURPOSE FIXING BAND



# Multi Purpose Fixing Band


Multi Purpose Fixing Band is a versatile product used in many applications. It is available in three widths 12, 17 & 26mm manufactured from Carbon Steel coated as standard used to secure cables, pipes, ducts & conduits. Available bare galvanised (G) or dip coated in Black (B), White (W), Red (R) and Orange (O). Other materials offered are Copper and Stainless Steel.

### **Multi Purpose Fixing Band**

- · High tensile strength
- Corrosion resistance
- Thick coating is kind to hands/cable
- · Easy to form around any section

Temperature Range: -15°C to 50°C

Material: Carbon Steel / PE Dip Coated



## Standard

Code	Width	Length (m)	Thickness	Fixing Hole Dia	Max Working Load (Kg)
ARB12G	12.0	10.0	0.8	5.0	75.0
ARB12B	12.0	10.0	0.8	5.0	75.0
ARB12R	12.0	10.0	0.8	5.0	75.0
ARB12W	12.0	10.0	0.8	5.0	75.0
ARB17G	17.0	10.0	0.8	7.0	95.0
ARB17B	17.0	10.0	0.8	7.0	95.0
ARB17R	17.0	10.0	0.8	7.0	95.0
ARB17W	17.0	10.0	0.8	7.0	95.0
ARB26G	26.0	10.0	0.8	8.0	200.0
ARB26B	26.0	10.0	0.8	8.0	200.0

### 304 Stainless Steel


Increased tensile strength and operating temperature

Temperature Range: -60°C to 160°C

Material: 304 Stainless Steel







### Stainless Steel

Code	Width	Length (m)	Thickness	Fixing Hole Dia	Max Working Load (Kg)
ARB12SS	12.0	10.0	0.8	5.0	75.0
ARB17SS	17.0	10.0	0.8	7.0	95.0

### Copper

Increased conductivity

Temperature Range: -15°C to 50°C

Material: Copper / Brass





#### Copper

Code	Width	Length (m)	Thickness	Fixing Hole Dia	Max Working Load (Kg)
ARB12C	12.0	10.0	0.8	5.0	65.0
ARB17C	17.0	10.0	0.8	7.0	85.0

Cable Glands

Tube Lugs

Tooling Earthing Lightning

Jointing

Heat-shrink

Conduit