

# GRIPLOC® METALLIC CABLE GLANDS | Cable Glands

## GRIPLOC® BRASS CABLE GLANDS

### Brass GripLoc® Glands Metric

- Standard Metric range of brass cable glands.
- GripLoc Seal® - Superior Ingress Protection, mechanical grip and cable retention.


**Standards:** EN 50262

**Protection:** IP69K / IP68 10 bar (150 PSI)

**Temperature Range:** -40°C to 100°C (static) (120° Instantaneous)

**Material (Gland):** Nickel-Plated Brass

**Material (Seal):** NBR Seal and EPDM O-Ring



Code	Cable Range (B)		Entry Thread		Gland	
	Min	Max	Size	Length (L1)	Length (L2)	A/F
GripLoc-BR-M12	2.0	5.0	M12 x 1.5	6.5	25.5	14.0
GripLoc-BR-M16	4.0	8.0	M16 x 1.5	6.0	27.0	19.0
GripLoc-BR-M20s	5.0	9.0	M20 x 1.5	6.0	29.0	22.0
GripLoc-BR-M20	6.0	12.0	M20 x 1.5	6.0	29.0	22.0
GripLoc-BR-M20L	10.0	14.0	M20 x 1.5	6.0	30.0	24.0
GripLoc-BR-M25	13.0	18.0	M25 x 1.5	7.0	32.0	30.0
GripLoc-BR-M32	18.0	25.0	M32 x 1.5	8.0	39.0	40.0
GripLoc-BR-M40	22.0	32.0	M40 x 1.5	8.0	45.0	50.0
GripLoc-BR-M50	32.0	38.0	M50 x 1.5	9.0	46.0	57.0
GripLoc-BR-M63	37.0	44.0	M63 x 1.5	10.0	48.0	68.0

### Brass GripLoc® Glands Metric - Long Thread

- Long Thread range of brass cable glands.
- GripLoc Seal® - Superior Ingress Protection, mechanical grip and cable retention.


**Standards:** EN 50262

**Protection:** IP69K / IP68 10 bar (150 PSI)

**Temperature Range:** -40°C to 100°C (static) (120° Instantaneous)

**Material (Gland):** Nickel-Plated Brass

**Material (Seal):** NBR Seal and EPDM O-Ring



Code	Cable Range (B)		Entry Thread		Gland	
	Min	Max	Size	Length (L1)	Length (L2)	A/F
GripLoc-BR-LT-M12	2.0	5.0	M12 x 1.5	10.0	29.0	14.0
GripLoc-BR-LT-M16	4.0	8.0	M16 x 1.5	10.0	31.0	19.0
GripLoc-BR-LT-M20s	5.0	9.0	M20 x 1.5	10.0	33.0	22.0
GripLoc-BR-LT-M20	6.0	12.0	M20 x 1.5	10.0	33.0	22.0
GripLoc-BR-LT-M20L	10.0	14.0	M20 x 1.5	10.0	34.0	24.0
GripLoc-BR-LT-M25	13.0	18.0	M25 x 1.5	12.0	37.0	30.0
GripLoc-BR-LT-M32	18.0	25.0	M32 x 1.5	12.0	43.0	40.0
GripLoc-BR-LT-M40	22.0	32.0	M40 x 1.5	15.0	52.0	50.0
GripLoc-BR-LT-M50	32.0	38.0	M50 x 1.5	15.0	52.0	57.0
GripLoc-BR-LT-M63	37.0	44.0	M63 x 1.5	15.0	53.0	68.0



Cable Glands  
Accs.  
Wiring Terminals  
Tube Lugs  
Tooling  
Earthing/Lightning  
Joining  
Heat-shrink  
Junction Boxes  
Cable Cleats  
Cable Ties  
MCC Cable  
Conduit  
Fixing & Security