

Cable Glands | GRIPLOC® NYLON CABLE GLANDS

METRIC GRIPLOC® NYLON ATEX CABLE GLANDS

Cable Glands
Accs.
Wiring Terminals
Tube Lugs
Tooling
Earthing Lightning
Joining
Heat-shrink
Junction Boxes
Cable Cleats
Cable Ties
MIOC Cable
Conduit
Fixing & Security



• Cap



• Seal



• Body




• Nitrile O-Ring



• Locknut

Nylon ATEX Exe Glands™ Metric


- ATEX Exe Metric range of nylon cable glands.
- For Hazardous Locations
- Standards:** EN 60079-0, EN 60079-7 EN 61241-0, EN 61241-1
- Device Group:** II
- Category:** 2 and 3
- Atmosphere:** G/D
- Zone:** 1, 2 - 21, 22 with flatseal
- Temperature Range:** -40°C to 100°C (static)
- Material (Gland):** PA (Nylon) UL 94
- Protection:** IP66 / IP68



Code	Cable Range (B)		Entry Thread	Gland		A/F
	Min	Max		Length (L1)	Length (L2)	
GripLoc-EX-M12	3.0	6.5	M12 x 1.5	8.0	29.0	15.0
GripLoc-EX-M16	4.0	8.0	M16 x 1.5	8.0	30.0	19.0
GripLoc-EX-M20	6.0	12.0	M20 x 1.5	9.0	36.0	24.0
GripLoc-EX-M20	10.0	14.0	M20 x 1.5	9.0	37.0	27.0
GripLoc-EX-M25	13.0	18.0	M25 x 1.5	11.0	42.0	33.0
GripLoc-EX-M32	18.0	25.0	M32 x 1.5	11.0	50.0	42.0
GripLoc-EX-M40	22.0	32.0	M40 x 1.5	13.0	61.0	53.0
GripLoc-EX-M50	32.0	38.0	M50 x 1.5	13.0	62.0	60.0
GripLoc-EX-M63	35.0	44.0	M63 x 1.5	14.0	63.0	68.0

Nylon ATEX Exe Glands™ Metric - Long Thread

- ATEX Exe Metric range of nylon cable glands.
- For Hazardous Locations
- Standards:** EN 60079-0, EN 60079-7 EN 61241-0, EN 61241-1
- Device Group:** II
- Category:** 2 and 3
- Atmosphere:** G/D
- Zone:** 1, 2 - 21, 22 with flatseal
- Temperature Range:** -40°C to 100°C (static)
- Material (Gland):** PA (Nylon) UL 94
- Protection:** IP66 / IP68



Code	Cable Range (B)		Entry Thread	Gland		A/F
	Min	Max		Length (L1)	Length (L2)	
GripLoc-EX-LT-M12	3.0	6.5	M12 x 1.5	15.0	36.0	15.0
GripLoc-EX-LT-M16	4.0	8.0	M16 x 1.5	15.0	37.0	19.0
GripLoc-EX-LT-M20	6.0	12.0	M20 x 1.5	15.0	42.0	24.0
GripLoc-EX-LT-M20	10.0	14.0	M20 x 1.5	15.0	43.0	27.0
GripLoc-EX-LT-M25	13.0	18.0	M25 x 1.5	15.0	46.0	33.0
GripLoc-EX-LT-M32	18.0	25.0	M32 x 1.5	15.0	54.0	42.0
GripLoc-EX-LT-M40	22.0	32.0	M40 x 1.5	18.0	66.0	53.0
GripLoc-EX-LT-M50	32.0	38.0	M50 x 1.5	18.0	67.0	60.0
GripLoc-EX-LT-M63	35.0	44.0	M63 x 1.5	18.0	67.0	68.0

GripLoc® brand cable glands are offered for sale exclusively in the United Kingdom by Remora Electrical Limited.