



Hooks

Suspension Hooks

Galvanised Steel Suspension Hooks


Suspension Hooks are designed for holding single power cables or small cable bundles. Fabricated from mild steel flat 6mm bar, hot dipped galvanised to BS EN ISO 1461:1999. Special designs are available on request.

The recommended safe working load for each hook is shown below.


- Holding single cables or small bundles to walls or supports structures
- Superior strength tensile strength
- Excellent stiffness

Temperature Range: -40°C to 150°C


Material: Mild Steel Hot Dipped Galvanised




Code	Cable Range		Dimensions			Material Size		Safe Working Load (Kg)
	Min	Max	(A)	(U)	(V)	(W)	Thickness	
SHA1	-	50.0	105.0	25.0	11.0	40.0	6.0	200.0
SHA2	51.0	75.0	120.0	25.0	13.0	50.0	6.0	200.0
SHA3	76.0	100.0	155.0	25.0	13.0	50.0	6.0	200.0
SHB1	-	50.0	125.0	55.0	11.0	40.0	6.0	200.0
SHB2	51.0	75.0	140.0	60.0	13.0	50.0	6.0	200.0
SHB3	76.0	100.0	150.0	60.0	13.0	50.0	6.0	200.0
SHC1	-	50.0	125.0	40.0	13.0	40.0	6.0	200.0
SHC2	51.0	75.0	140.0	45.0	13.0	50.0	6.0	200.0
SHC3	76.0	100.0	150.0	45.0	13.0	50.0	6.0	200.0



Type SHA



Type SHB



Type SHC