
## Single Fixing Aluminium Two-Part Single-Fixing

## **LM6 Aluminium**

The One Hole Cable Clamps are designed to fix cables 10mm to 70mm diameter. Manufactured from LM6 aluminium to BS1490. They are fully stackable and specifically designed to mount directly to channel, ladder or any flat surface.






## **Single Fixing - Aluminium**

- Fastening/fitting/routing single and multiple conductor low, medium and high voltage cables
- Excellent weathering and corrosion resistance
- Excellent stiffness
- Excellent tensile strength
- Fully recyclable

Standards: European Standard IEC 61914:2009 Temperature Range: -60°C to 150°C

Material: Aluminium LM6





Aluminium	Cable Range			Dimensions			
	Min	Max	Stud Hole Size	(A)	(B)	(C)	(D)
1ALM1	10.0	13.0	M10	28.0	41.0	43.0	17.0
1ALM2	13.0	16.0	M10	30.0	44.0	43.0	17.0
1ALM3	16.0	19.0	M10	32.0	47.0	43.0	17.0
1ALM4	19.0	22.0	M10	34.0	50.0	43.0	17.0
1ALM5	22.0	25.0	M10	36.0	53.0	43.0	17.0
1ALM6	25.0	32.0	M10	39.0	61.0	43.0	17.0
1ALM7	32.0	38.0	M10	44.0	67.0	43.0	17.0
1ALM8	38.0	44.0	M10	50.0	72.0	43.0	14.0
1ALM9	44.0	51.0	M10	57.0	78.0	43.0	14.0
1ALM10	51.0	57.0	M10	68.0	84.0	43.0	14.0
1ALM11	57.0	64.0	M10	75.0	91.0	43.0	14.0
1ALM12	64.0	70.0	M10	81.0	93.0	43.0	14.0



Wiring Terminals

Tooling

Earthing Lightning

Jointing Heat-shrink