


METRIC NYLON ADAPTORS AND REDUCERS



Metric-Metric Nylon Adaptors

Remora Metric-Metric Nylon Adaptors enable the use of larger cable glands with smaller pre-existing threaded holes in machines, devices and housings.

Protection: IP56

IP66 (if fitted with sealing washer)

Temperature Range: -40°C to 100°C (static)

Material: PA6 (Nylon)



Code	Male Thread	Female Thread	Male Thread Length (L1)	A/F	Body Height
AM12M16N	M12 x 1.5	M16 x 1.5	9.0	20.0	18.0
AM16M20N	M16 x 1.5	M20 x 1.5	9.0	24.0	18.0
AM20M25N	M20 x 1.5	M25 x 1.5	9.0	29.0	18.0
AM25M32N	M25 x 1.5	M32 x 1.5	10.0	26.0	18.0
AM32M40N	M32 x 1.5	M40 x 1.5	12.0	36.0	18.0
AM40M50N	M40 x 1.5	M50 x 1.5	12.0	55.0	18.0
AM50M63N	M50 x 1.5	M63 x 1.5	14.0	68.0	18.0

Metric-Metric Nylon Reducers

Remora Metric-Metric Nylon Reducers enable the use of smaller cable glands with larger pre-existing threaded holes in machines, devices and housings.

Protection: IP56

IP66 (if fitted with sealing washer)

Temperature Range: -40°C to 100°C (static)

Material: PA6 (Nylon)



Code	Male Thread	Female Thread	Male Thread Length (L1)	A/F	Body Height
RM16M12N	M16 x 1.5	M12 x 1.5	9.0	20.0	7.0
RM20M12N	M20 x 1.5	M12 x 1.5	9.0	24.0	7.0
RM20M16N	M20 x 1.5	M16 x 1.5	9.0	24.0	7.0
RM25M16N	M25 x 1.5	M16 x 1.5	10.0	29.0	7.0
RM25M20N	M25 x 1.5	M20 x 1.5	10.0	29.0	7.0
RM32M16N	M32 x 1.5	M16 x 1.5	12.0	36.0	7.0
RM32M20N	M32 x 1.5	M20 x 1.5	12.0	36.0	7.0
RM32M25N	M32 x 1.5	M25 x 1.5	12.0	36.0	7.0
RM40M20N	M40 x 1.5	M20 x 1.5	12.0	46.0	7.0
RM40M25N	M40 x 1.5	M25 x 1.5	12.0	46.0	7.0
RM40M32N	M40 x 1.5	M32 x 1.5	12.0	46.0	7.0
RM50M20N	M50 x 1.5	M20 x 1.5	14.0	55.0	7.0
RM50M25N	M50 x 1.5	M25 x 1.5	14.0	55.0	7.0
RM50M32N	M50 x 1.5	M32 x 1.5	14.0	55.0	7.0
RM50M40N	M50 x 1.5	M40 x 1.5	14.0	55.0	7.0
RM63M32N	M63 x 1.5	M32 x 1.5	15.0	65.0	7.0
RM63M40N	M63 x 1.5	M40 x 1.5	15.0	65.0	7.0
RM63M50N	M63 x 1.5	M50 x 1.5	15.0	65.0	7.0