## 316 Stainless Steel - Uncoated

- Salt spray, corrosion & weather resistant
- Outstanding chemical resistance

**Temperature Range:** -80°C to 500°C
**Material:** 316 Stainless Steel
**Standards:** UL Certification E227552 / DNV Certification E-6729

Stainless Steel Tie Base *(see p.244)*

| Code | Length (A) | Width (B) | Max Bundle Dia. | Loop Tensile Strength (Kg) | N |
|---|---|---|---|---|---|
| SSCT200x4.6 | 200 | 4.6 | 50.0 | 68.0 | 667.0 |
| SSCT360x4.6 | 360 | 4.6 | 102.0 | 68.0 | 667.0 |
| SSCT360x7.9 | 360 | 7.9 | 102.0 | 136.0 | 1,335.0 |
| SSCT520x7.9 | 520 | 7.9 | 152.0 | 136.0 | 1,335.0 |

## 316 Stainless Steel - Coated

- Salt spray, corrosion & weather resistant
- Outstanding chemical resistance

**Temperature Range:** -80°C to 150°C
**Material:** 316 Stainless Steel
**Coating:** Pure Polyester/Epoxy
**Standards:** UL Certification E227552 / DNV Certification E-6729

| Code | Length (A) | Width (B) | Max Bundle Dia. | Loop Tensile Strength (Kg) | N |
|---|---|---|---|---|---|
| SSCT200x4.6-COATED | 200 | 4.6 | 50.0 | 68.0 | 667.0 |
| SSCT360x4.6-COATED | 360 | 4.6 | 102.0 | 68.0 | 667.0 |
| SSCT360x7.9-COATED | 360 | 7.9 | 102.0 | 136.0 | 1,335.0 |
| SSCT520x7.9-COATED | 520 | 7.9 | 152.0 | 136.0 | 1,335.0 |

## 316 Stainless Steel - Coated

- Salt spray, corrosion & weather resistant
- Outstanding chemical resistance

**Temperature Range:** -80°C to 150°C
**Material:** 316 Stainless Steel
**Coating:** Pure Polyester/Epoxy
**Standards:** UL Certification E227552 / DNV Certification E-6729

| Code | Length (A) | Width (B) | Max Bundle Dia. | Loop Tensile Strength (Kg) | N |
|---|---|---|---|---|---|
| SSCT200x4.6-COATED-* | 200 | 4.6 | 50.0 | 68.0 | 667.0 |
| SSCT360x4.6-COATED-* | 360 | 4.6 | 102.0 | 68.0 | 667.0 |
| SSCT360x7.9-COATED-* | 360 | 7.9 | 102.0 | 136.0 | 1,335.0 |
| SSCT520x7.9-COATED-* | 520 | 7.9 | 152.0 | 136.0 | 1,335.0 |

## How To Order

SSCT360x4.6 - COATED - R

Code prefix

Colour

BL = Blue
GR= Green
R = Red
Y = Yellow