

Heatshrink & Repair | PVC SLEEVING

WHAT'S NEW IN... PVC SLEEVING

PVC Sleevings

Coloured PVC Sleevings

Our RoHS compliant high grade PVC flexible Earth Sleevings is manufactured from premium virgin grade compound in a wide range of sizes. Standard nominal wall size is 0.5mm, other sizes are available to order. Supplied with green and yellow stripes for use in earth identification and solid colour for electrical contracting purposes. Supplied in continuous 100m coils. Some sizes are available supplied on reels, please contact us for more information



Green/Yellow and Coloured PVC Sleevings

- Dielectric Strength:** 12 kV/mm min
- Temperature Range:** -20°C to 85°C
- Elongation at Break:** 220% min
- Insulation Resistance:** 10¹⁰ ohm/cm
- Operating Temperature:** 20 kV/mm
- Hardness:** BSS20-30
- Flammability:** Self-extinguishing in 30 seconds
- Standards:** BS 2848/3/85T
- Material:** PVC
- Colour:** Green/Yellow, Black, Blue, Brown, Yellow, Grey, Red, Green, White



Code	Reel Code	Internal Diameter	To Cover Cable Size mm ²	Coil Length (m)
PVC-2.0-G/Y	PVC-R-2.0-G/Y	2.0		100
PVC-3.0-G/Y	PVC-R-3.0-G/Y	3.0	0.5-0.75	100
PVC-4.0-G/Y	PVC-R-4.0-G/Y	4.0	1.5-2.5	100
PVC-6.0-G/Y		6.0	6.0	100
PVC-8.0-G/Y		8.0	10.0	100
PVC-10.0-G/Y		10.0	16.0-25.0	100

Code	Reel Code	Internal Diameter	To Cover Cable Size mm ²	Coil Length (m)
PVC-2.0-*	PVC-R-2.0-*	2.0		100
PVC-3.0-*	PVC-R-3.0-*	3.0	0.5-0.75	100
PVC-4.0-*	PVC-R-4.0-*	4.0	1.5-2.5	100
PVC-6.0-*		6.0	6.0	100
PVC-8.0-*		8.0	10.0	100
PVC-10.0-*		10.0	16.0-25.0	100

How To Order

