

### Brass Locknuts

Brass Locknuts are recommended for use in securing brass cable glands, unions, thread converters and stopping plugs. Manufactured from extrusion brass (BS 2874 CZ121 Pb3) and available in both a plain finish or with a corrosion resistant nickel plating.

**Temperature Range:** -60°C to 200°C

**Material:** Brass BS 2874 CZ121 Pb3

**Finish:** Plain Brass or Nickel Plated



Brass		Nickel Plated Brass			
Code	Code	Entry Thread	A/F	A/C	Thickness
UBLN12	BLN12	M12 x 1.5	15.0	16.5	3.0
UBLN16	BLN16	M16 x 1.5	20.0	22.0	3.5
UBLN1	BLN1	M20 x 1.5	24.0	26.5	4.0
UBLN2	BLN2	M25 x 1.5	32.0	35.0	3.5
UBLN3	BLN3	M32 x 1.5	40.0	44.0	4.0
UBLN4	BLN4	M40 x 1.5	46.0	50.0	4.5
UBLN5	BLN5	M50 x 1.5	65.0	72.0	5.0
UBLN6	BLN6	M63 x 1.5	75.0	82.0	6.5
UBLN7	BLN7	M75 x 1.5	88.0	98.0	6.5
UBLN8	BLN8	M80 x 2.0	97.0	109.0	8.0
UBLN9	BLN9	M90 x 2.0	112.0	125.0	10.0
UBLN10	BLN10	M100 x 2.0	-	-	-

NPT		Nickel Plated Brass			
Code	Code	Entry Thread	A/F	A/C	Thickness
UBLN050NPT	BLN050NPT	½" NPT	27.0	29.0	3.0
UBLN075NPT	BLN075NPT	¾" NPT	30.0	33.0	4.0
UBLN100NPT	BLN100NPT	1" NPT	35.5	40.0	6.0
UBLN125NPT	BLN125NPT	1¼" NPT	46.0	50.5	6.0
UBLN150NPT	BLN150NPT	1½" NPT	55.0	60.5	6.0
UBLN200NPT	BLN200NPT	2" NPT	65.0	71.0	6.0
UBLN250NPT	BLN250NPT	2½" NPT	90.0	99.0	9.0
UBLN300NPT	BLN300NPT	3" NPT	104.0	115.0	9.0
UBLN350NPT	BLN350NPT	3½" NPT	114.0	125.0	10.0

### Nickel Plated Brass

Code	Entry Thread	A/F	A/C	Thickness
BLNPG7	PG7 x 1.27	15.0	16.5	3.0
BLNPG9	PG9 x 1.41	18.0	20.0	3.0
BLNPG11	PG11 x 1.41	21.0	24.0	3.0
BLNPG13	PG13.5 x 1.41	23.0	26.0	3.0
BLNPG16	PG16 x 1.41	26.0	30.0	3.0
BLNPG21	PG21 x 1.59	32.0	36.0	3.5
BLNPG29	PG29 x 1.59	41.0	45.0	4.0
BLNPG36	PG36 x 1.59	51.0	57.0	5.0
BLNPG42	PG42 x 1.59	60.0	65.0	5.0
BLNPG48	PG48 x 1.59	64.0	69.0	6.0

