

CCG PosiFlex Cable Gland

The Posi-Flex Cable Gland is designed for use with unarmoured, elastomeric and plastic cables. Manufactured from brass and encapsulated with a non-corrosive polyester outer body, offering complete protection in the most hostile of environments. Seals on cable outer sheath, to IP 68 if fitted with sealing washer.

- For use in highly corrosive environments.
- All exposed brass parts encapsulated in a non-corrosive body.
- Wide sealing range.
- Complete with a fitted elastomeric seal and washer providing IP68 protection.
- Supplied complete with IP sealing washer.

Standards: EN 50262 IEC 62444
 BS 6121 Part 1 MASC 11-303

Installation: AS/NZS 3000 BS 7430
 BS 6121-5 IEC 60364-5-54
 BS 7671 SANS 0142

Marine: ABS 14-SG246753-2-PDA / DNV-GL TAE000000Z




London Underground Approval: 3043

Protection: IP66 / IP67 / IP68 (2m cont.) ~ MASC 11-263

Temperature Range: -20°C to 125°C

Material (Gland): Brass (Nickel Plated) Encapsulated in Glass Reinforced Polyester

Material (Seal): Thermoset Elastomer



Code	Reference		Cable OD (B)		Gland Length (L2)	Thread Entry (C)	Length (L1)	A/F	A/C
	Size	Min	Max						
053800	00 - 20ss	3.0	8.0		43.0	M20 x 1.5	10.0	30.0	34.0
0538-0	0 - 20s	7.0	11.5		43.0	M20 x 1.5	10.0	30.0	34.0
053801	1 - 20	11.0	15.0		47.0	M20 x 1.5	10.0	34.0	38.0
053802	2 - 25	15.0	20.0		50.0	M25 x 1.5	10.0	42.0	47.0
053803	3 - 32	20.0	26.5		60.0	M32 x 1.5	10.0	52.0	59.0
053804	4 - 40	26.0	34.0		72.0	M40 x 1.5	15.0	62.0	70.0

