
NYLON DOME HEAD STOPPING PLUGS





Metric Nylon Dome Head Stopping Plugs

Remora industrial dome head stopping plugs are designed as a cost effective permanent solution for blanking unused pre-threaded holes. A 'cross' slot in the cap enables tightening with a screwdriver. **Protection:** IP56

rotection: IP56

IP66 (if fitted with sealing washer) Temperature Range: -40°C to 100°C (static)

Material: PA6 (Nylon)

Colour: Grey



Entry Thread	Thread Length (L1)	Cap Diameter (A)
M12 x 1.5	8.5	15.0
M16 x 1.5	8.5	19.0
M20 x 1.5	9.0	25.0
M25 x 1.5	10.5	30.0
M32 x 1.5	10.5	38.0
M40 x 1.5	11.5	46.0
M50 x 1.5	13.5	56.0
M63 x 1.5	14.0	68.0
	M12 x 1.5 M16 x 1.5 M20 x 1.5 M25 x 1.5 M32 x 1.5 M40 x 1.5 M50 x 1.5	M12 x 1.5 8.5 M16 x 1.5 8.5 M20 x 1.5 9.0 M25 x 1.5 10.5 M32 x 1.5 10.5 M40 x 1.5 11.5 M50 x 1.5 13.5

PG Nylon Dome Head Stopping Plugs

Remora industrial dome head stopping plugs are designed as a cost effective permanent solution for blanking unused pre-threaded holes. A 'cross' slot in the cap enables tightening with a screwdriver.

Protection: IP56

IP66 (if fitted with sealing washer)

Temperature Range: -40°C to 100°C (static) Material: PA6 (Nylon)

Colour: Grey



Code	Entry Thread	Thread Length (L1)	Cap Diameter (A)
VS7	PG7 x 1.27	8.5	15.0
VS9	PG9 x 1.41	8.5	19.0
VS11	PG11 x 1.41	9.0	22.0
VS13	PG13.5 x 1.41	9.0	25.0
VS16	PG16 x 1.41	10.5	27.0
VS21	PG21 x 1.59	10.5	33.0
VS29	PG29 x 1.59	11.5	44.0
VS36	PG36 x 1.59	13.5	55.0
VS42	PG42 x 1.59	13.5	62.0
VS48	PG48 x 1.59	14.5	68.0



