

PG-Metric Hazardous Adaptors

Enlarges housing entry thread.

- PG - ISO Metric range.

- Application; Hazardous Area, Machines, Devices, Housings, Panels

Standards: IECEx: Ex d I/IIC Mb/Gb, Ex e I/IIC Mb/Gb, Ex t IIIC Db

ATEX: Ex d IIC Gb, Ex e IIC Gb, Ex tb IIIC Db, II 2 GD

Protection: IP66 / IP67 / IP68 (2m cont.)

Temperature Range: -20°C to 95°C

Material: Brass or Nickel Plated Brass



Code	Entry Thread		Thread Length		Hex Length		
	Male	Female	Male (L1)	Female (F)	A/F	A/C	Min (G)
APG9M20E-UN	PG9	M20 x 1.5	15.0	15.0	27.0	29.3	21.0
APG11M20E-UN	PG11	M20 x 1.5	15.0	15.0	27.0	29.3	21.0
APG13M20E-UN	PG13.5	M20 x 1.5	15.0	15.0	27.0	29.3	21.0
APG13M25E-UN	PG13.5	M25 x 1.5	15.0	15.0	36.0	40.3	21.0
APG16M25E-UN	PG16	M25 x 1.5	15.0	15.0	36.0	40.3	21.0
APG21M32E-UN	PG21	M32 x 1.5	15.0	15.0	45.0	49.6	21.0
APG29M40E-UN	PG29	M40 x 1.5	15.0	15.0	55.0	62.0	21.0
APG36M50E-UN	PG36	M50 x 1.5	15.0	15.0	60.0	67.2	21.0
APG42M63E-UN	PG42	M63 x 1.5	15.0	15.0	70.0	78.8	21.0
APG48M63E-UN	PG48	M63 x 1.5	15.0	15.0	70.0	78.8	21.0

PG-Metric Hazardous Reducers

Reduces housing entry thread.

- PG - ISO Metric range.

- Application; Hazardous Area, Machines, Devices, Housings, Panels

Standards: IECEx: Ex d I/IIC Mb/Gb, Ex e I/IIC Mb/Gb, Ex t IIIC Db

ATEX: Ex d IIC Gb, Ex e IIC Gb, Ex tb IIIC Db, II 2 GD

Protection: IP66 / IP67 / IP68 (2m cont.)

Temperature Range: -20°C to 95°C

Material: Brass or Nickel Plated Brass



Code	Entry Thread		Thread Length		Hex Length		
	Male	Female	Male (L1)	Female (F)	A/F	A/C	Min (G)
RPG16M20E-UN	PG16	M20 x 1.5	15.0	15.0	32.0	36.0	7.0
RPG21M20E-UN	PG21	M20 x 1.5	15.0	15.0	35.0	39.0	7.0
RPG21M25E-UN	PG21	M25 x 1.5	15.0	15.0	36.0	40.7	7.0
RPG29M20E-UN	PG29	M20 x 1.5	15.0	15.0	51.0	53.7	7.0
RPG29M25E-UN	PG29	M25 x 1.5	15.0	15.0	51.0	53.7	7.0
RPG29M32E-UN	PG29	M32 x 1.5	15.0	15.0	51.0	61.9	7.0
RPG36M20E-UN	PG36	M20 x 1.5	15.0	15.0	55.0	67.0	7.0
RPG36M25E-UN	PG36	M25 x 1.5	15.0	15.0	55.0	61.9	7.0
RPG36M32E-UN	PG36	M32 x 1.5	15.0	15.0	55.0	61.9	7.0
RPG36M40E-UN	PG36	M40 x 1.5	15.0	15.0	55.0	61.9	7.0
RPG42M20E-UN	PG42	M20 x 1.5	15.0	15.0	70.0	78.8	7.0
RPG42M25E-UN	PG42	M25 x 1.5	15.0	15.0	70.0	78.8	7.0
RPG42M32E-UN	PG42	M32 x 1.5	15.0	15.0	70.0	78.8	7.0
RPG42M40E-UN	PG42	M40 x 1.5	15.0	15.0	70.0	78.8	7.0
RPG42M50E-UN	PG42	M50 x 1.5	15.0	15.0	70.0	78.8	7.0
RPG48M32E-UN	PG48	M32 x 1.5	15.0	15.0	80.0	90.0	7.0
RPG48M40E-UN	PG48	M40 x 1.5	15.0	15.0	80.0	90.0	7.0
RPG48M50E-UN	PG48	M50 x 1.5	15.0	15.0	80.0	90.0	7.0

