

# Heatshrink & Repair | HEATSHRINK SLEEVING

## HEATSHRINK SLEEVING KITS

### Heatshrink Mini Kits RMK1

This kit includes 73 pieces x 100mm long in EU colours, Black, Blue, Brown, Grey, Green/ Yellow and White. All supplied in a handy plastic tray. Sizes from 2.5mm to 13mm supplied diameter. 2:1 Shrink Ratio, UL Approved, Flame Retardant, RoHS compliant.

**Temperature Range:** -40°C to 135°C

**Material:** Flame Retardant Polyolefin

**Colour:** Black, Blue, Brown, Grey, Green/Yellow, White



Code	Internal Diameter		Box Quantity	Heatshrink Length	Kit Contents
	Max Before Shrink	Min After Shrink			
RMK1	2.5	1.25	20	100	4 x Black, Blue, Brown, Grey, Green/Yellow
	3.0	1.5	15	100	3 x Black, Brown, Grey, Green/Yellow 6x Blue
	5.0	2.5	10	100	2 x Black, Blue, Brown, Grey, Green/Yellow
	6.0	3.0	8	100	2 x Black, Blue, Brown, Grey
	10.0	5.0	10	100	2 x Black, Blue, Brown, Grey, White
	13.0	6.5	10	100	2 x Black, Blue, Brown, Grey, White

### Heatshrink Mini Kits RMK2

Our adhesive lined heatshrink kit contains 35 x 100mm pieces, it is designed to protect electrical and mechanical components against moisture and water. All supplied in a handy plastic tray. Sizes from 3.0mm to 19mm supplied diameter. 3:1 Shrink Ratio, RoHS compliant.

**Temperature Range:** -55°C to 110°C

**Material:** Flame Retardant Polyolefin

**Colour:** Black or Red



Code	Internal Diameter		Quantity	Heatshrink Length	Kit Contents
	Max Before Shrink	Min After Shrink			
RMK2	3.0	1.0	18	100	14 x Black 4 x Red
	6.0	2.0	9	100	6 x Black 3 x Red
	9.0	3.0	4	100	3 x Black 1 x Red
	12.0	4.0	2	100	1 x Black, 1 x Red
	19.0	6.0	2	100	1 x Black, 1 x Red

### Hot Air Heat Guns

The Iroda flame less heat gun has a piezoelectric self-starting ignition system. Powered by the refill cell of a disposable lighter. Windproof flame and waterproof ignition. Handy compact size and easy to use. Uses Butane fuel (not included).

**Applications:** Compact size, ideal for quick heatshrink applications.

The Steinel HL 1820S is a multi-purpose heat gun with cool air stage and choice of 2 temperature settings for convenient hand-held or bench work. The exclusive DuraTherm™ heating element ensures long life and even heat. • 3 Stage Switch • Duratherm™ Heating Element • Sleek, balanced design for comfortable long-term use • Non-Slip Soft Stand

**Applications:** Ideal for soldering, de-soldering and heat-shrinking

Code	Description	Dimensions	Heat Temperature	Voltage
HSG1	Mini Heatshrink Gun	115 x 80 x 25	Up to 650°C	N/A
HSG2	Steinel HL 1810S Heat Gun	260 x 90 x 25	Three Stage 50°C, 400°C & 600°C	230-240V, 50Hz
HSGNOZZLE1	HL 1810S Surface Nozzle	50mm Surface		
HSGNOZZLE2	HL 1810S Reflector Nozzle	39mm Reflector		

