


GRIPLOC® NYLON CABLE GLANDS | Cable Glands

METRIC GRIPLOC® NYLON ATEX CABLE GLANDS

Nylon ATEX Exe Glands™ Metric - Blue

- ATEX Exe Metric range of nylon cable glands.
 - For Hazardous Locations
- Standards:** EN 60079-0, EN 60079-7, EN 60079-31
Device Group: II
Category: 2 and 3
Atmosphere: G/D
Zone: 1, 2 - 21, 22
Temperature Range: -20°C to 80°C (static)
Material (Gland): PA (Nylon) UL 94
Material (Seal): Silicone
Protection: IP66 / IP68



Code	Cable Range (B)		Entry Thread	Gland		
	Min	Max	Size	Length (L1)	Length (L2)	A/F
GripLoc-EX-M12-BL	3.0	6.5	M12 x 1.5	8.0	29.0	15.0
GripLoc-EX-M16-BL	4.0	8.0	M16 x 1.5	8.0	30.0	19.0
GripLoc-EX-M20-BL	6.0	12.0	M20 x 1.5	9.0	36.0	24.0
GripLoc-EX-M25-BL	13.0	18.0	M25 x 1.5	11.0	42.0	33.0
GripLoc-EX-M32-BL	18.0	25.0	M32 x 1.5	11.0	50.0	42.0
GripLoc-EX-M40-BL	22.0	32.0	M40 x 1.5	13.0	61.0	53.0
GripLoc-EX-M50-BL	32.0	38.0	M50 x 1.5	13.0	62.0	60.0
GripLoc-EX-M63-BL	37.0	44.0	M63 x 1.5	14.0	63.0	68.0



Call the Remora sales team at 01226 352 000

Challenge us - We find a solution

Cable Glands
Accs.
Wiring Terminals
Tube Lugs
Tooling
Earthing/Lighting
Joining
Heat-shrink
Junction Boxes
Cable Cleats
Cable Ties
MCC Cable
Conduit
Fixing & Security