



MICC RGM Cable Glands (Heavy Duty)

Remora RGM Glands are designed to be used with mineral insulated cables. They are precision manufactured from high quality extrusion brass and approved for hazardous areas.

Hazardous: Atex Zones 1 & 2 EExd


Classification: Ex II 2G EExd IIC

Certification: BS EN 60702-2:2002, BS EN 50014:1997 (A1-A2), BS EN 50018:2000
ATEX Directive 94/9/EC

Protection: IP54

Temperature Range: -20°C to 450°C

Material: Brass BS 2874



Code	Entry Thread Size	Length	Cap Diameter
RGM2H1.5	M20 x 1.5	10.0	18.5
RGM2H2.5	M20 x 1.5	10.0	18.5
RGM2H4.0	M20 x 1.5	10.0	18.5
RGM2H4.0-M25	M25 x 1.5	10.0	24.0
RGM2H6	M20 x 1.5	10.0	18.5
RGM2H6-M25	M25 x 1.5	10.0	24.0
RGM2H10-M25	M25 x 1.5	10.0	24.0
RGM2H10-M32	M32 x 1.5	10.0	27.0
RGM3H1.5	M20 x 1.5	10.0	18.5
RGM3H2.5	M20 x 1.5	10.0	18.5
RGM3H2.5-M25	M25 x 1.5	10.0	24.0
RGM3H4.0	M20 x 1.5	10.0	18.5
RGM3H4-M25	M25 x 1.5	10.0	24.0
RGM3H6-M25	M25 x 1.5	10.0	24.0
RGM3H10-M25	M25 x 1.5	10.0	24.0
RGM3H10-M32	M32 x 1.5	10.0	27.0
RGM4H1.5	M20 x 1.5	10.0	18.5
RGM4H2.5	M20 x 1.5	10.0	18.5
RGM4H2.5-M25	M25 x 1.5	10.0	24.0
RGM4H4-M25	M25 x 1.5	10.0	24.0
RGM4H6-M25	M25 x 1.5	10.0	24.0
RGM4H6-M32	M32 x 1.5	10.0	27.0
RGM4H10-M25	M25 x 1.5	10.0	24.0
RGM4H10-M32	M32 x 1.5	10.0	27.0

