

Imperial (ET)-Metric Hazardous Adaptors and Reducers

Enlarges and reduces housing entry threads.

• Imperial (ET) - ISO Metric range.

• Application: Hazardous Area, Machines, Devices, Housings, Panels

• Standards: IECEx:Ex d I/IIC, EX e I/IIC, EX tb IIC Db

ATEX: I m2, Ex d IMb, Ex e I Mb, or II G, Ex d IIC Gb, Exe IIC Gb, Ex tb IIC Db

Protection: IP66 / IP68

Temperature Range: -20°C to 65°C



Code	Entry Thread		Thread Length				Hex Length	
	Male	Female	Male (L1)	Female (F)	A/F	A/C	Min (G)	
RET050M16E-UN	½" / 0.50 ET	M16 x 1.5	15.0	15.0	19.0	22.0	21.0	
RET050M20E-UN	½" / 0.50 ET	M20 x 1.5	15.0	15.0	24.0	27.5	21.0	
RET075M20E-UN	¾" / 0.75 ET	M20 x 1.5	15.0	15.0	24.0	27.5	21.0	
RET075M25E-UN	¾" / 0.75 ET	M25 x 1.5	15.0	15.0	30.5	35.0	21.0	
RET100M20E-UN	1" / 1.00 ET	M20 x 1.5	15.0	15.0	30.5	35.0	5.0	
RET100M25E-UN	1" / 1.00 ET	M25 x 1.5	15.0	15.0	30.5	35.0	5.0	
RET125M20E-UN	1¼" / 1.25 ET	M20 x 1.5	15.0	15.0	38.0	42.0	5.0	
RET125M25E-UN	1¼" / 1.25 ET	M25 x 1.5	15.0	15.0	38.0	42.0	5.0	
RET150M20E-UN	1½" / 1.50 ET	M20 x 1.5	15.0	15.0	42.5	49.0	5.0	
RET150M25E-UN	1½" / 1.50 ET	M25 x 1.5	15.0	15.0	42.5	49.0	5.0	

