

WHAT'S NEW IN... SEALING WASHERS

Sealing Washers

Sealing washers form a mechanical seal between the cable gland and equipment panel. This can fill irregularities between "less-than-perfect" mating surfaces forming a liquid tight seal and evenly distributing pressure over the mating surface. The requirement for a sealing washer will depend on the ingress protection rating or code of protection for the equipment the gland is being fitted to.

Remora offers a comprehensive range of sealing and locking washers to suit every purpose.



Nylon Sealing Washers

• ISO Metric range. Standard Nylon sealing washer.

Standards: FDA and BFR Compliant UL94 HB

Temperature Range: -40°C to 85°C

Material: PA6 Nylon (ISO 1043)



Code	Gland Entry	ID (A)	OD (B)
NW16	M16	16.5	25.0
NW20	M20	20.5	30.0
NW25	M25	25.5	36.0
NW32	M32	32.5	42.5
NW40	M40	40.5	52.0
NW50	M50	50.5	64.5
NW63	M63	63.5	80.0
NW75	M75	75.5	95.0

HDPE Sealing Washers


• ISO Metric range. Increased temperature range.

Standards: UL94 HB

DIN 8075

Temperature Range: -40°C to 100°C (static)

Material: High Density Polyethylene (HDPE DIN 8075)



Code	Gland Entry	ID (A)	OD (B)
805516	M16	16.2	23.0
805520	M20	20.2	27.0
805525	M25	25.2	35.0
805532	M32	32.2	43.0
805540	M40	40.3	53.0
805550	M50	50.3	67.0
805563	M63	63.3	85.0
805575	M75	75.3	95.0