

## PG BRASS ADAPTORS AND REDUCERS

### PG-Metric Industrial Adaptors

- PG-ISO Metric range.
- Application; Machines, Devices, Housings, Panels


**Standards:** EN 50262

**Protection:** IP54


IP66 (if fitted with sealing washer)

**Temperature Range:** -60°C to 200°C

**Material:** Nickel Plated Brass



Code	Entry Thread		Thread Length		A/F	Body Height
	Male	Female	Male (L1)	Female (F)		
APG9M16S	PG9 x 1.41	M16 x 1.5	13.0	13.0	24.0	15.0
APG9M20S	PG9 x 1.41	M20 x 1.5	13.0	13.0	24.0	15.0
APG11M16S	PG11 x 1.41	M16 x 1.5	13.0	13.0	24.0	15.0
APG11M20S	PG11 x 1.41	M20 x 1.5	13.0	13.0	24.0	15.0
APG13M20S	PG13.5 x 1.41	M20 x 1.5	13.0	13.0	24.0	15.0
APG13M25S	PG13.5 x 1.41	M25 x 1.5	13.0	13.0	24.0	15.0
APG16M25S	PG16 x 1.41	M25 x 1.5	13.0	13.0	29.0	15.0
APG21M32S	PG21 x 1.59	M32 x 1.5	13.0	13.0	36.0	15.0
APG29M40S	PG29 x 1.59	M40 x 1.5	13.0	15.0	44.0	17.5
APG36M50S	PG36 x 1.59	M50 x 1.5	13.0	15.0	54.0	17.5
APG42M63S	PG42 x 1.59	M63 x 1.5	13.0	15.0	70.0	17.5



### PG-Metric Industrial Reducers

- PG-ISO Metric range.
- Application; Machines, Devices, Housings, Panels

**Standards:** EN 50262

**Protection:** IP54


IP66 (if fitted with sealing washer)

**Temperature Range:** -60°C to 200°C

**Material:** Nickel Plated Brass



Code	Entry Thread		Thread Length		A/F	Body Height
	Male	Female	Male (L1)	Female (F)		
RPG16M20S	PG16 x 1.41	M20 x 1.5	13.0	24.5	4.0	
RPG21M20S	PG21 x 1.59	M20 x 1.5	13.0	30.3	5.5	
RPG21M25S	PG21 x 1.59	M25 x 1.5	13.0	30.3	5.5	
RPG29M20S	PG29 x 1.59	M20 x 1.5	13.0	39.0	5.5	
RPG29M25S	PG29 x 1.59	M25 x 1.5	13.0	39.0	5.5	
RPG29M32S	PG29 x 1.59	M32 x 1.5	13.0	39.0	5.5	
RPG36M25S	PG36 x 1.59	M25 x 1.5	13.0	50.0	5.5	
RPG36M32S	PG36 x 1.59	M32 x 1.5	13.0	50.0	5.5	
RPG36M40S	PG36 x 1.59	M40 x 1.5	13.0	50.0	5.5	
RPG42M32S	PG42 x 1.59	M32 x 1.5	13.0	57.0	5.5	
RPG42M40S	PG42 x 1.59	M40 x 1.5	13.0	57.0	5.5	
RPG42M50S	PG42 x 1.59	M50 x 1.5	13.0	57.0	5.5	
RPG48M32S	PG48 x 1.59	M32 x 1.5	13.0	62.3	5.5	
RPG48M40S	PG48 x 1.59	M40 x 1.5	13.0	62.3	5.5	
RPG48M50S	PG48 x 1.59	M50 x 1.5	13.0	62.3	5.5	



Call the Remora sales team at **01226 352 000**

Challenge us - We find a solution