

METALLIC CONDUIT | Flexible Conduit Systems

FLEXIBLE GALVANISED STEEL CONDUIT

Flexible Conduit - Galvanised Steel

- Square locked galvanised steel conduit, good mechanical stability and extreme flexibility.


Temperature Range: -50°C to 300°C

Crush Resistance: 1500N

IP Rating: IP40

Material: Galvanised Steel to DIN 53210

Standards: EN 50086



Code	Conduit Size	Conduit ID	Conduit OD	Coil Lengths (m)
CC16/*	16	13.0	17.0	10 / 30 / 50
CC20/*	20	17.0	21.0	10 / 30 / 50
CC25/*	25	22.0	27.0	10 / 30 / 50
CC32/*	32	28.0	32.0	10 / 30
CC40/*	40	38.0	43.0	10 / 30
CC50/*	50	48.0	55.0	10 / 30
CC63/10	63	57.0	63.0	10
CC75/10	75	70.0	75.0	10
CC100/10	100	93.0	100.0	10



Contractor Packs

- Pack consists of 10 meter of PVC coated steel conduit and 10 straight fittings including 10 locknuts.


Temperature Range: -20°C to 80°C

Crush Resistance: 1500N

IP Rating: IP54

Material: Galvanised Steel to DIN 53210 / PVC Coating

Standards: EN 50086



Code	Conduit Size	Conduit ID	Conduit OD	Coil (m)
CON/GALV/PVC/20	20	17.0	21.0	10
CON/GALV/PVC/25	25	22.0	27.0	10



Flexible Conduit - Galvanised Steel PVC Covered

- Square locked galvanised steel conduit with PVC cover, good mechanical stability and flexibility.

Temperature Range: -20°C to 80°C

Crush Resistance: 1500N

IP Rating: IP54

Material: Galvanised Steel to DIN 53210 / PVC Coating

Standards: EN 50086



Code	Conduit Size	Conduit ID	Conduit OD	Coil Lengths (m)
FPCC16/*	16	13.0	17.0	10 / 30 / 50
FPCC20/*	20	17.0	21.0	10 / 30 / 50
FPCC25/*	25	22.0	27.0	10 / 30 / 50
FPCC32/*	32	28.0	34.0	10 / 30
FPCC40/*	40	38.0	43.0	10 / 30
FPCC50/*	50	48.0	55.0	10 / 30
FPCC63/10	63	57.0	65.0	10
FPCC75/10	75	70.0	77.0	10
FPCC100/10	100	93.0	102.0	10



Call the Remora sales team at **01226 352 000**

Challenge us - We find a solution

Cable Glands
Accs.
Wiring Terminals
Tube Lugs
Tooling
Earthing/Lighting
Joining
Heat-shrink
Junction Boxes
Cable Cleats
Cable Ties
MCC Cable
Conduit
Fixing & Security