PVC SLEEVING | Heatshrink&Repair

MULTI-REEL PVC SLEEVING



Multi-Reel Multi-Reel PVC Sleeving

The PVC Multi Reel is designed with electricians in mind. It is supplied on one reel, which is split into 3 sections. Our RoHS compliant high grade PVC flexible Earth Sleeving is manufactured from premium virgin grade compound and is available in diameters of 2.0mm, 3.0mm or 4.0mm. The 2.0mm and 3.0mm contains 20 metres Blue & Brown Sleeving and 60 metres Green/Yellow sleeving. The 4.0mm contains 10 metres Blue & Brown Sleeving and 40 metres Green/Yellow sleeving.

Green/Yellow and Coloured PVC Sleeving

Dielectric Strength: 12 kV/mm min Temperature Range: -20°C to 85°C Elongation at Break: 220% min

Insulation Resistance: 1010 ohm/cm Operating Temperature: 20 kV/mm

Hardness: BSS20-30

Flammability: Self-extinguishing in 30 seconds

Standards: BS 2848/3/85T

Material: PVC

Colour: Green/Yellow, Blue & Brown







(m

Code	Internal Diameter	To Cover Cable Size mm ²	Blue & Brown	Green/Yellow
PVC-MR-2.0	2.0		20	60
PVC-MR-3.0	3.0	0.5-0.75	20	60
PVC-MR-4.0	4.0	1.5-2.5	10	40

Cable Glands

Accs.

Tooling

Jointing

Conduit

