



Fixing Band

Multi-Purpose Fixing Band

Multi-Purpose Fixing Band is a versatile product used in many applications. It is available in three widths 12, 17 & 26mm manufactured from Carbon Steel coated as standard used to secure cables, pipes, ducts & conduits. Available bare galvanised (G) or coated in Black (B), White (W), Red (R) and Orange (O). Other materials offered are Copper and Stainless Steel.

Multi-Purpose Fixing Band

- High tensile strength
- Corrosion resistance
- Coating is kind to hands/cable
- Easy to form around any section

Temperature Range: -15°C to 50°C


Material: Carbon Steel / PE Coated

Standards: BS 7671:2018



Standard

Code	Width (W)	Length (m)	Thickness	Fixing Hole Dia (F)	Centers (L1)	Max Working Load (Kg)
ARB12G	12.0	10.0	0.8	5.0	15.0	75.0
ARB12B	12.0	10.0	0.8	5.0	15.0	75.0
ARB12R	12.0	10.0	0.8	5.0	15.0	75.0
ARB12W	12.0	10.0	0.8	5.0	15.0	75.0
ARB17G	17.0	10.0	0.8	7.0	20.0	95.0
ARB17B	17.0	10.0	0.8	7.0	20.0	95.0
ARB17R	17.0	10.0	0.8	7.0	20.0	95.0
ARB17W	17.0	10.0	0.8	7.0	20.0	95.0
ARB26G	26.0	10.0	0.8	8.0	28.0	200.0
ARB26B	26.0	10.0	0.8	8.0	28.0	200.0



304 Stainless Steel

- Increased tensile strength and operating temperature

Temperature Range: -60°C to 160°C

Material: 304 Stainless Steel



• 316 Stainless Steel version available on request

Stainless Steel

Code	Width (W)	Length (m)	Thickness	Fixing Hole Dia (F)	Max Working Load (Kg)
ARB12SS	12.0	10.0	0.8	5.0	75.0
ARB17SS	17.0	10.0	0.8	7.0	95.0

Copper

- Increased conductivity

Temperature Range: -15°C to 50°C

Material: Copper / Brass



Copper

Code	Width (W)	Length (m)	Thickness	Fixing Hole Dia (F)	Max Working Load (Kg)
ARB12C	12.0	10.0	0.8	5.0	65.0
ARB17C	17.0	10.0	0.8	7.0	85.0