


# Cable Glands | GRIPLOC® NYLON CABLE GLANDS

## METRIC GRIPLOC® NYLON ATEX CABLE GLANDS

### Nylon ATEX Exe Glands™ Metric

- ATEX Exe Metric range of nylon cable glands.
- For Hazardous Locations
- Standards:** EN 60079-0, EN 60079-7, EN 60079-31
- Device Group:** II
- Category:** 2 and 3
- Atmosphere:** G/D
- Zone:** 1, 2 - 21, 22
- Temperature Range:** -20°C to 80°C (static)
- Material (Gland):** PA (Nylon) UL 94
- Material (Seal):** Silicone
- Protection:** IP66 / IP68



| Code           | Cable Range (B) |      | Entry Thread |             | Gland       |      |
|----------------|-----------------|------|--------------|-------------|-------------|------|
|                | Min             | Max  | Size         | Length (L1) | Length (L2) | A/F  |
| GripLoc-EX-M12 | 3.0             | 6.5  | M12 x 1.5    | 8.0         | 29.0        | 15.0 |
| GripLoc-EX-M16 | 4.0             | 8.0  | M16 x 1.5    | 8.0         | 30.0        | 19.0 |
| GripLoc-EX-M20 | 6.0             | 12.0 | M20 x 1.5    | 9.0         | 36.0        | 24.0 |
| GripLoc-EX-M25 | 13.0            | 18.0 | M25 x 1.5    | 11.0        | 42.0        | 33.0 |
| GripLoc-EX-M32 | 18.0            | 25.0 | M32 x 1.5    | 11.0        | 50.0        | 42.0 |
| GripLoc-EX-M40 | 22.0            | 32.0 | M40 x 1.5    | 13.0        | 61.0        | 53.0 |
| GripLoc-EX-M50 | 32.0            | 38.0 | M50 x 1.5    | 13.0        | 62.0        | 60.0 |
| GripLoc-EX-M63 | 37.0            | 44.0 | M63 x 1.5    | 14.0        | 63.0        | 68.0 |

• Cap

• Seal

• Body

• Nitrile O-Ring

• Locknut



GripLoc® brand cable glands are offered for sale exclusively in the United Kingdom by Remora Electrical Limited.