

## WHAT'S NEW IN... HEATSHRINK CABLE END CAPS

# End Caps

## Heatshrink Cable End Caps

Remora Heatshrink end caps are manufactured from cross-linked polyolefin material and are coated with a hot melt adhesive on the inner surface. This provides a water tight seal against the damage of moisture, dirt or corrosion. The rugged wall of these end caps also offers excellent resistance against abrasion. Suitable for use on polymeric and paper insulated, lead jacketed cables.



### Heatshrink Cable End Caps

- Good chemical resistance
- Good solvent resistance
- Unaffected by UV light

**Dielectric Strength:** 12 kV/mm min  
**Temperature Range:** -55°C to 100°C  
**Shrink Temperature:** +120°C

**Tensile Strength:** 12.0 MPa min


**Tensile Strength After Heat Ageing:** 168 hours @ 120°C - 10 MPa min

**Elongation:** 300% min

**Elongation After Heat Ageing:** 168 hours @ 120°C - 250% min

**Material:** Cross-linked Polyolefin

**Colour:** Black



Code	Internal Diameter		Shrunk	
	Max Before Shrink	Min After Shrink	Wall Thickness	Length
HSEC10	10.0	3.5	3.0	34.0
HSEC15	15.0	4.5	3.0	44.0
HSEC20	20.0	8.0	3.0	69.0
HSEC35	35.0	15.0	3.0	93.0
HSEC55	55.0	25.0	3.3	107.0
HSEC75	75.0	35.0	3.3	127.0
HSEC100	100.0	50.0	4.0	152.0
HSEC120	120.0	60.0	4.0	152.0
HSEC148	148.0	57.0	4.0	152.0
HSEC160	160.0	82.0	4.0	152.0