

HAZARDOUS AREA STOPPING PLUGS | Accessories

METRIC and NPT HAZARDOUS AREA HEX HEAD PLUGS

Metric Hazardous Hex Head Stopping Plug - Brass

- ISO Metric range.
- Application; Hazardous Area, Machines, Devices, Housings, Panels

Standards: IECEx: Exd I/IIc MbGb, Ex e I/IIc MbGb, Ex t IIIC Db
ATEX: Exd IMb, Ex e I Mb, or II GD, Ex d IIC Gb


Protection: Tested to IP68 (if fitted with sealing washer)

Temperature Range: -20°C to 95°C

Material: Brass or Nickel Plated Brass



Code	Entry Thread	Thread Length (L1)	A/F	A/C
STPDH16-UN	M16 x 1.5	15.0	20.0	22.0
STPDH20-UN	M20 x 1.5	15.0	24.0	27.0
STPDH25-UN	M25 x 1.5	15.0	28.0	33.0
STPDH32-UN	M32 x 1.5	15.0	38.0	43.0
STPDH40-UN	M40 x 1.5	15.0	47.0	54.0
STPDH50-UN	M50 x 1.5	15.0	56.0	64.0
STPDH63-UN	M63 x 1.5	15.0	70.0	81.0
STPDH75-UN	M75 x 1.5	17.5	80.0	101.0
STPDH80-UN	M80 x 2.0	20.0	90.0	103.5
STPDH90-UN	M90 x 2.0	20.0	95.0	109.4
STPDH100-UN	M100 x 2.0	20.0	105.0	121.0



NPT Hazardous Hex Head Stopping Plug - Brass

- National Pipe Thread (NPT) range.
- Application; Hazardous Area, Machines, Devices, Housings, Panels

Standards: IECEx: Exd I/IIc MbGb, Ex e I/IIc MbGb, Ex t IIIC Db
ATEX: Exd IMb, Ex e I Mb, or II GD, Ex d IIC Gb

Protection: Tested to IP66 (if fitted with sealing washer)

Temperature Range: -20°C to 95°C

Material: Brass or Nickel Plated Brass



Code	Entry Thread	Thread Length (L1)	A/F	A/C
STPDH0.50NPT-UN	½" / 0.50 NPT	20.0	24.0	27.5
STPDH0.75NPT-UN	¾" / 0.75 NPT	20.0	28.0	33.0
STPDH1.00NPT-UN	1" / 1.00 NPT	24.0	38.5	43.0
STPDH1.25NPT-UN	1¼" / 1.25 NPT	25.0	48.0	54.0
STPDH1.50NPT-UN	1½" / 1.50 NPT	26.0	56.0	64.5
STPDH2.00NPT-UN	2" / 2.00 NPT	27.0	70.1	80.8
STPDH2.50NPT-UN	2½" / 2.50 NPT	40.5	80.1	92.1
STPDH3.00NPT-UN	3" / 3.00 NPT	42.0	101.6	117.0

