

Terminals | HEAT SHRINKABLE RING TERMINALS

WHAT'S NEW IN... HEAT SHRINKABLE INSULATED TERMINALS

Heat Shrinkable Ring and Fork Terminals


Made from oxygen-free high conductivity copper, these terminals are electro-tin plated for excellent conductivity and resistance to corrosion. Push-on terminals are made from brass, the insulated types have an additional internal copper sleeve, ensuring insulation support and a good crimp joint.



Heat Shrinkable Ring Terminals

Heat shrinkable ring terminals.

Temperature Range: -40°C to 105°C
Material: Tin Plated Electrolytic Copper / Vinyl
Colour: Red, Blue, Yellow
Standards: DIN 46288 Part 4



Code	Colour	Range mm ²	ID (A)	ID (B)	Length (L1)	Length (L2)	Width (W)
HSRR40	Red	0.5-1.5	1.7	4.3	9.5	28.5	8.0
HSRR50		0.5-1.5	1.7	5.3	9.5	28.5	8.0
HSRR60		0.5-1.5	1.7	6.4	15.7	34.7	11.6
HSRR80		0.5-1.5	1.7	8.4	19.5	38.5	13.6
HSRR100		0.5-1.5	1.7	10.5	19.5	38.5	13.6
HSBR40	Blue	1.5-2.5	2.3	4.3	10.8	29.8	8.5
HSBR50		1.5-2.5	2.3	5.3	10.8	29.8	9.5
HSBR60		1.5-2.5	2.3	6.4	15.6	34.6	12.0
HSBR80		1.5-2.5	2.3	8.4	15.6	34.6	12.0
HSBR100		1.5-2.5	2.3	10.5	19.5	38.5	13.6
HSBR120	1.5-2.5	2.3	13.0	24.4	43.4	19.2	
HSYR40	Yellow	4.0-6.0	3.5	4.3	9.6	33.6	9.5
HSYR50		4.0-6.0	3.5	5.3	9.6	33.6	9.5
HSYR60		4.0-6.0	3.5	6.4	12.3	36.3	12.0
HSYR80		4.0-6.0	3.5	8.4	21.4	45.4	15.0
HSYR100		4.0-6.0	3.5	10.5	21.4	45.4	15.0
HSYR120		4.0-6.0	3.5	13.0	22.5	46.5	19.2