
## **EARTHING POINTS**



## **Earth Blocks**

Remora Earth blocks allow earth conductor termination or live conductor termination (within a suitable housing). Manufactured from brass with corrosion resistant nickel plated finish.

Cable Size: 16mm<sup>2</sup>
Material: Brass CZ121 Pb3
Finish: Nickel Plated





Code	Cable Entry Hole Diameters		Length (L2)	Width
EBL004	1 x 6.5	3 x 5.5	51.0	20.0
EBL008	2 x 6.5	6 x 5.5	88.0	20.0



# **Earth Bosses**


Remora Earth Bosses are designed to provide an earth connection point on a steel structure.

The boss can welded onto steel vessels, tanks and other structures

Material: Mild Steel to 970 230M07 grade EN1A

Fixings: Stainless Steel 316L

Standards: BS 7430



#### Mild Steel

Code	Length	Diameter	Thread Size	
EBMS2525	25.0	25.0	M8	
EBMS3030	30.0	30.0	M8	
EBMS3040	30.0	40.0	M10	
EBMS4030	40.0	30.0	M10	
EBMS4040	40.0	40.0	M12	
EBMS5040	50.0	40.0	M10	
EBMS5050	50.0	50.0	M10	

### Stainless Steel

Code	Length	Diameter	Thread Size	
EBSS2525	25.0	25.0	M8	
EBSS3030	30.0	30.0	M8	
EBSS3040	30.0	40.0	M10	
EBSS4030	40.0	30.0	M10	
EBSS4040	40.0	40.0	M12	
EBSS5040	50.0	40.0	M10	
EBSS5050	50.0	50.0	M10	

Š

Wiring Terminals

\_

Earthin

ointing

Heatshrink

o c

Cable

Cable

Onduit

Securit