


HEAT SHRINKABLE RING TERMINALS | Terminals

HEAT SHRINKABLE INSULATED TERMINALS



Heat Shrinkable Fork Terminals

Heat shrinkable fork terminals.



Temperature Range: -40°C to 105°C

Material: Tin Plated Electrolytic Copper / Vinyl

Colour: Red, Blue, Yellow

Standards: DIN 46288 Part 4




Code	Colour	Range mm ²	ID (A)	ID (B)	Length (L1)	Length (L2)	Width (W)
HSRF40	Red	0.5-1.5	1.7	4.3	14.0	33.0	8.1
HSRF50		0.5-1.5	1.7	5.3	14.0	33.0	9.5
HSBF40	Blue	1.5-2.5	2.3	4.3	14.0	33.0	7.9
HSBF50		1.5-2.5	2.3	5.3	14.0	33.0	9.3
HSYF40	Yellow	4.0-6.0	3.4	4.3	12.7	33.0	9.0
HSYF50		4.0-6.0	3.4	5.3	12.7	36.7	9.0
HSYF60		4.0-6.0	3.4	6.4	12.7	36.7	9.0



Heat Shrinkable Solder Sleeve

Heat shrinkable solder sleeve.



Temperature Range: -40°C to 105°C

Material: Tin Plated Electrolytic Copper / Vinyl

Colour: Red, Blue, Yellow, White

Standards: DIN 46288 Part 4



Code	Colour	Range mm ²	Length (L2)	Min (A)	Wire Min	Wire Max
HSSOLW	White	0.25-.034	26.0	1.7	0.4	1.7
HSSOLR	Red	0.5-1.0	40.0	2.7	1.3	1.2
HSSOLB	Blue	1.5-2.5	40.0	4.5	1.8	2.0
HSSOLY	Yellow	4.0-6.0	40.0	6.0	2.3	3.4

Call the Remora sales team at **01226 352 000**

Challenge us - We find a solution