HEATSHRINK CABLE END CAPS

End Caps

Heatshrink Cable End Caps

Remora Heatshrink end caps are manufactured from cross-linked polyolefin material and are coated with a hot melt adhesive on the inner surface. This provides a water tight seal against the damage of moisture, dirt or corrosion. The rugged wall of these end caps also offers excellent resistance against abrasion. Suitable for use on polymeric and paper insulated, lead jacketed cables.

Heatshrink Cable End Caps

- Good chemical resistance
- Good solvent resistance
- Unaffected by UV light
- 2:1 Shrink Ratio
- Zero Halogen

Dielectric Strength: 12 kV/mm min
Temperature Range: -55°C to 100°C
Shrink Temperature: +120°C
Tensile Strength: 12.0 MPa min
Tensile Strength After Heat Ageing: 68 hours @ 120°C - 10 MPa min
Elongation: 300% min
Elongation After Heat Ageing: 168 hours @ 120°C - 250% min
Material: Cross-linked Polyolefin. Internally Coated with Hot Melt Adhesive
Colour: Black

Code	Internal Diameter Max Before Shrink	Min After Shrink	Shrunk Wall Thickness	Length
HSEC12	12.0	4.0	2.6	40.0
HSEC20	20.0	6.0	2.2	42.0
HSEC25	25.0	8.5	2.5	65.0
HSEC40	40.0	15.0	3.3	75.0
HSEC55	55.0	25.0	3.3	107.0
HSEC75	75.0	35.0	3.3	127.0
HSEC100	100.0	50.0	4.0	152.0
HSEC120	120.0	60.0	4.0	152.0
HSEC148	148.0	57.0	4.0	152.0
HSEC160	160.0	82.0	4.0	152.0