

HAZARDOUS AREA MALE - MALE ADAPTORS

Hazardous Area Male to Male Adaptor

Male to Male Adaptors provide a connection between two female threads of the same or dissimilar thread forms. Manufactured from high quality brass and supplied with IP sealing washer as standard.

- An IP rating of IP66 /67/68 is maintained.
- Supplied with sealing washer as standard.

Hazardous: IECEx: Ex d I/IIc Mb/Gb, Ex e I/IIc Mb/Gb, Ex t IIIC Db
ATEX: Ex d IIC Gb, Ex e IIC Gb, Ex tb IIIC Db, II 2 GD

Certification: IECEx ITA 13.0005X IEC 60079-0, IEC 60079-1, IEC 60079-7, IEC 60079-31
ATEX CML15ATEX1040X EN 60079-0, EN 60079-1, EN 60079-7, EN 60079-31



IP Protection: IP66 / IP68 (2m)

IP Protection -Tapered Thread: IP65

Temperature Range: -20°C to 95°C

Material: Brass / Nickel Plated Brass



Code	Male Thread		Male Thread		Overall	
	(A)	Min Length (L1)	(B)	Min Length (L1)	Length (L2)	A/F
CM16M16E-UN	M16 x 1.5	15.0	M16 x 1.5	15.0	40.0	24.0
CM20M20E-UN	M20 x 1.5	15.0	M20 x 1.5	15.0	40.0	27.0
CM25M25E-UN	M25 x 1.5	15.0	M25 x 1.5	15.0	40.0	32.0
CM32M32E-UN	M32 x 1.5	15.0	M32 x 1.5	15.0	40.0	38.0
CM20N050E-UN	M20 x 1.5	15.0	½" / 0.50 NPT	15.0	40.0	27.0
CM25N075E-UN	M25 x 1.5	15.0	¾" / 0.75 NPT	15.0	40.0	32.0
CM32N100E-UN	M32 x 1.5	15.0	1" / 1.00 NPT	19.0	44.0	38.0
CN050N050E-UN	½" / 0.50 NPT	15.0	½" / 0.50 NPT	15.0	40.0	25.0
CN075N075E-UN	¾" / 0.75 NPT	15.0	¾" / 0.75 NPT	15.0	40.0	32.0
CN100N100E-UN	1" / 1.00 NPT	19.0	1" / 1.00 NPT	19.0	48.0	38.0



Call the Remora sales team at **01226 352 000**

Challenge us - We find a solution