

Terminals | PRE-INSULATED BULLET CONNECTORS

PRE-INSULATED CRIMP TERMINALS

Pre-Insulated Bullet Connectors

Made from oxygen-free high conductivity copper, these terminals are electro-tin plated for excellent conductivity and resistance to corrosion. Push-on terminals are made from brass, the insulated types have an additional internal copper sleeve, ensuring insulation support and a good crimp joint.



Pre-Insulated Male Bullet Terminals


Bullet terminal connectors provide a secure and reliable connection by mating a female and male wire terminal.

Temperature Range: -10°C to 75°C

Material: Tin Plated Electrolytic Copper / Vinyl

Voltage: 300V

Colour: Red, Blue, Yellow



Code	Colour	Range mm ²	ID (A)	Length (L1)	Length (L2)	Width (W)
RBU40	Red	0.5-2.5	1.7	11.0	21.0	4.0
BBU40	Blue	1.5-2.5	2.3	11.2	21.0	4.0
BBU50		1.5-2.5	2.3	10.7	21.0	5.0
YBU50	Yellow	4.0-6.0	3.4	11.0	25.5	5.0



Pre-Insulated Female Bullet Terminals


Bullet terminal connectors provide a secure and reliable connection by mating a female and male wire terminal.

Temperature Range: -10°C to 75°C

Material: Tin Plated Electrolytic Copper / Vinyl

Voltage: 300V

Colour: Red, Blue, Yellow



Code	Colour	Range mm ²	ID (A)	Length (L1)	Length (L2)	Width (W)
RBR40	Red	0.5-2.5	1.7	12.8	25.5	3.9
BBR40	Blue	1.5-2.5	2.3	12.8	25.5	3.9
BBR50		1.5-2.5	2.3	12.8	25.5	4.9
YBR50	Yellow	4.0-6.0	3.4	12.6	28.0	4.9



Pre-Insulated Butt Connectors


Double ended female wire terminals that create a simple connection by mating two wires together.

Temperature Range: -10°C to 75°C

Material: Tin Plated Electrolytic Copper / Vinyl

Voltage: 600V

Colour: Red, Blue, Yellow



Code	Colour	Range mm ²	ID (A)	Length (L2)	Width (W)
RBC	Red	0.5-1.5	1.8	24.5	4.3
BBC	Blue	1.5-2.5	2.4	24.5	4.8
YBC	Yellow	4.0-6.0	3.5	27.0	6.7