

NPT-Metric Hazardous Adaptors

Enlarges housing entry thread.

• NPT - ISO Metric range.

• Application; Hazardous Area, Machines, Devices, Housings, Panels

• **Standards:** IECEx: Ex db I Mb / Ex eb I Mb / Ex db IIC Gb / Ex eb IIC Gb

ATEX: I M2 Ex db I Mb / Ex eb I Mb, II 2 GD Ex db IIC Gb

• **Protection:** IP66 / IP68 (2m cont.) BS EN 62444


• **Temperature Range:** -20°C to 95°C (-60°C to 160°C with High Temp Gasket)

• **Material:** Brass or Nickel Plated Brass (Marine Grade)



Code	Entry Thread		Thread Length				Hex Length	
	Male	Female	Male (L1)	Female (F)	A/F	A/C	Min (G)	
AN050M20E-UN	½" / 0.50 NPT	M20 x 1.5	15.0	15.0	27.0	30.4	21.0	
AN075M25E-UN	¾" / 0.75 NPT	M25 x 1.5	15.0	15.0	32.0	36.0	21.0	

• For Nickel Plated remove -UN when ordering



Cable
Glands

Accs.

Wiring
Terminals

Tube
Lugs

Tooling

Earthing
Lightning

Joining

Heat-
shrink

Junction
Boxes

Cable
Cleats

Cable
Ties

MCC
Cable

Conduit

Fixing &
Security