

# Accessories | HEX HEAD STOPPING PLUGS

## INDUSTRIAL AREA METRIC



### Hex Head Nylon Stopping Plugs

Remora industrial hex head stopping plugs are designed as a cost effective permanent solution for blanking unused pre-threaded holes.

**Protection:** IP56

IP66 (if fitted with sealing washer)

**Temperature Range:** -40°C to 100°C (static)

**Material:** PA6 (Nylon)

**Colour:** Black or White



Black Code	White Code	Entry Thread	Thread Length (L1)	A/F	A/C
NSTP16	NSTP16W	M16 x 1.5	11.0	19.0	22.0
NSTP20	NSTP20W	M20 x 1.5	11.0	23.0	26.0
NSTP25	NSTP25W	M25 x 1.5	11.0	28.0	32.0
NSTP32	NSTP32W	M32 x 1.5	11.0	36.0	41.0

### Hex Head Brass Stopping Plugs

Remora industrial hex head stopping plugs are designed as a cost effective permanent solution for blanking unused pre-threaded holes.

**Standards:** EN 50262

**Protection:** IP54

IP66 (if fitted with sealing washer)

**Temperature Range:** -60°C to 200°C

**Material:** Nickel Plated Brass



Code	Entry Thread	Thread Length (L1)	A/F
STPH16	M16 x 1.5	12.0	18.0
STPH20	M20 x 1.5	13.0	22.0
STPH25	M25 x 1.5	13.0	27.0
STPH32	M32 x 1.5	16.0	34.0
STPH40	M40 x 1.5	18.0	43.0
STPH50	M50 x 1.5	18.0	54.0
STPH63	M63 x 1.5	18.0	68.0
STPH75	M75 x 1.5	20.0	80.0