

Accessories | HAZARDOUS AREA DOME STOPPING PLUGS

HAZARDOUS AREA DOME STOPPING PLUGS



Metric Hazardous Dome Head Stopping Plug - Brass

- ISO Metric range.
- Application; Hazardous Area, Machines, Devices, Housings, Panels
- Standards:** IECEx: Ex db I Mb / Ex eb I Mb / Ex db IIC Gb / Ex eb IIC Gb
ATEX: I M2 Ex db I Mb / Ex eb I Mb, II 2 GD Ex db IIC Gb
- Protection:** IP66 / IP68 (2m cont.) BS EN 62444
- Temperature Range:** -20°C to 95°C (-60°C to 160°C with High Temp Gasket)
- Material:** Brass or Nickel Plated Brass (Marine Grade)



Code	Entry Thread	Thread Length (L1)	Head Diameter	Allen Key AF
353016-UN	M16 x 1.5	16.0	22.0	10.0
353020-UN	M20 x 1.5	16.0	25.0	10.0
353025-UN	M25 x 1.5	16.0	35.0	10.0
353032-UN	M32 x 1.5	16.0	42.0	10.0
353040-UN	M40 x 1.5	16.0	50.0	10.0
353050-UN	M50 x 1.5	16.0	60.0	10.0
353063-UN	M63 x 1.5	16.0	70.0	14.0
353075-UN	M75 x 1.5	16.0	85.0	14.0
353080-UN	M80 x 2.0	20.0	90.0	14.0
353090-UN	M90 x 2.0	20.0	100.0	14.0
353100-UN	M100 x 2.0	20.0	110.0	14.0

- For Nickel Plated remove -UN when ordering



Metric Hazardous Dome Head Stopping Plug - Nylon

- ISO Metric range.
- Application; Machines, Devices, Housings, Panels
- Standards:** IECEx: Exe IIC Gb, Ex nR IICGc, Ex tb IIIC Db
ATEX: II 2 GD, Ex e IIC Gb, Ex tb IIIC, II3 GD, Ex nRIIC GC
- Protection:** IP66 / IP68
- Temperature Range:** -20°C to 95°C
- Material:** Glass Filled Nylon



Code	Entry Thread	Thread Length (L1)	Head Diameter	Allen Key AF
352716	M16 x 1.5	15.0	20.5 (min)	6.0
352720	M20 x 1.5	12.0	28.0 (min)	10.0
352725	M25 x 1.5	15.0	33.0 (min)	10.0
352732	M32 x 1.5	15.0	40.0 (min)	10.0
352740	M40 x 1.5	15.0	46.0 (min)	19.0
352750	M50 x 1.5	15.0	56.0 (min)	19.0
352763	M63 x 1.5	15.0	69.0 (min)	19.0
352775	M75 x 1.5	15.0	81.0 (min)	19.0

