


Cable Cleats | METALLIC TREFOIL

TREFOIL CABLE CLEATS



Trefoil Single-Fixing

The Aluminium Trefoil Cleat is designed for cleating three single cables in a trefoil configuration where low to medium short circuit withstand levels are required. The range covers cables from 24.0 to 76.0mm overall diameter.



Single Bolt Fixing - Aluminium

Standards: European Standard IEC 61914:2009

Temperature Range: -60°C to 150°C

Material: Aluminium LM6



Aluminium Code	Cable Range		Stud Hole Size	Dimensions		
	Min	Max		(A)	(B)	(C)
376AC01	24.0	25.0	M10	94.0	75.0	38.0
376AC02	25.0	27.0	M10	97.0	75.0	38.0
376AC03	27.0	28.0	M10	100.0	75.0	38.0
376AC04	28.0	30.0	M10	103.0	76.0	38.0
376AC05	30.0	32.0	M10	105.0	79.0	38.0
376AC06	32.0	34.0	M10	106.0	83.0	38.0
376AC07	34.0	35.0	M10	109.0	86.0	38.0
376AC08	35.0	36.0	M10	113.0	89.0	38.0
376AC09	36.0	38.0	M10	116.0	92.0	38.0
376AC10	38.0	40.0	M10	119.0	95.0	38.0
376AC11	40.0	41.0	M10	122.0	99.0	38.0
376AC12	41.0	43.0	M10	124.0	105.0	38.0
376AC13	43.0	44.0	M10	127.0	108.0	38.0
376AC14	44.0	46.0	M10	130.0	112.0	38.0
376AC15	46.0	48.0	M10	133.0	114.0	38.0
376AC16	48.0	49.0	M10	137.0	118.0	38.0
376AC17	49.0	51.0	M10	140.0	121.0	38.0
376AC18	51.0	53.0	M10	143.0	124.0	38.0
376AC19	53.0	54.0	M10	146.0	127.0	38.0
376AC20	54.0	55.5	M10	155.0	133.0	44.0
376AC21	55.5	57.0	M10	158.0	137.0	44.0
376AC22	57.0	59.0	M10	160.0	141.0	44.0
376AC23	59.0	60.0	M10	163.0	145.0	44.0
376AC24	60.0	62.0	M10	165.0	148.0	44.0
376AC25	62.0	63.5	M10	168.0	152.0	44.0
376AC26	63.5	65.0	M10	172.0	156.0	44.0
376AC27	65.0	66.5	M10	176.0	160.0	44.0
376AC28	66.5	68.0	M10	178.0	164.0	44.0
376AC29	68.0	70.0	M10	181.0	168.0	44.0
376AC30	70.0	71.5	M10	187.0	171.0	44.0
376AC31	71.5	73.0	M10	190.0	175.0	44.0
376AC32	73.0	74.5	M10	193.0	179.0	44.0
376AC33	74.5	76.0	M10	197.0	183.0	44.0