

ELECTRICAL TAPES | Heatshrink & Repair

TAPES and UNDERGROUND MARKING

Gaffer / Duct Tape

- Adhesive coated with vacuum hotmelt (synthetic rubber)
 - Ideal for fixing, binding and repairs
 - Water resistant, highly adhesive and leaves no residue. Suitable for interior and exterior use
- Material:** Polycloth
Temperature: -15°C to +70°C **Tensile Strength:** >60 N/cm **Elongation:** 10-20%



Code	Colour	Length (m)	Width (mm)	Thickness (mm)
GT48-B	Black	50	48	0.18
GT48-S	Silver	50	48	0.18
GT48-W	White	50	48	0.18



Hazard Warning Tape

- Ideal for marking floors, walls and overhead
 - Flexible
 - Good water and abrasion resistance. 3kV voltage resistance.
- Material:** PVC film coated with rubber pressure sensitive adhesive
Temperature: -15°C to +80°C **Tensile Strength:** >16 N/cm **Elongation:** 150%



Code	Colour	Length (m)	Width (mm)	Thickness (mm)
HWT50-BY	Black/Yellow	33	50	0.15



DENSO Waterproof Tape

- Denso tape offers a weatherproof seal when wrapped around joints to stop the ingress of moisture.
Material: Synthetic - Impregnated and coated with neutral petroleum compound
Colour: Black



Code	Width	Length (m)
DENSO-50mm	50.0	10



Underground Warning Tape

- Manufactured from low density polyethylene Lead free pigments with virgin grade film Soil tolerance from pH 2.5 to pH 11.0 inclusive 100 micron grade is manufactured in accordance with ENATS 12-23
Material: Polyethylene (PE) Film
Colour: Yellow



Code	Width	Length (m)	Colour	Thickness (micron)
WT-01	150.0	365	Yellow	50



Tiletape Underground Warning

- Tiletape combines a highly visible warning plus a measure of protection in one system. Ideal for lower voltage electric cables and other utilities. Zero PVC content.

- Highly resistant to Acids and Alkalis
- Base Substrate:** Recycled Plastic
Toptape Substrate: 100% Virgin Polyethylene
Tensile Strength: 10MN/M²
Wording: CAUTION ELECTRIC CABLE BELOW



Code	Width	Length (m)	Thickness
TT150	150.0	40	2.5

