



# Heatshrink

## Adhesive Lined Dual Wall

Adhesive Lined Dual Wall Heatshrink is a semi-rigid, heat shrinkable polyolefin tubing that is co-extruded and selectively cross-linked to provide an integral, melt-able inner wall. Uses include strain relief for wire terminations, connections and harness breakouts.

### Adhesive Lined Dual Wall Heatshrink

Adhesive Lined Heatshrink is designed to insulate and seal electrical and mechanical products against water and moisture. Dual-Wall 3:1 shrink ratio, flame-retardant, inner liner of hot melt adhesive. UL approved and RoHS compliant.


- Medium Wall 3:1 Shrink Ratio

**Temperature Range:** -55°C to 110°C

**Material:** Flame Retardant Polyolefin (UL94 - V-0)

**Shrinkage Temp:** 120°C

**Colour:** Black



Code	Nominal	Internal Diameter		Shrunk	
	Diameter	Max Before Shrink	Min After Shrink	Wall Thickness	Length (m)
HSAL3-B	3.0	3.0	1.0	1.0	1.2
HSAL6-B	6.0	6.0	2.0	1.0	1.2
HSAL12-B	12.0	12.0	4.0	1.6	1.2
HSAL19-B	19.0	19.0	6.0	2.0	1.2
HSAL30-B	30.0	33.0	10.0	2.4	1.2
HSAL40-B	40.0	43.0	12.0	2.5	1.2
HSAL50-B	50.0	52.0	19.0	2.5	1.2

