

Heatshrink & Repair | HEATSHRINK SLEEVING

HEATSHRINK SLEEVING KITS

Heatshrink Mini Kits RMK1

This kit includes 73 pieces x 100mm long in EU colours, Black, Blue, Brown, Grey, Green/Yellow and White. All supplied in a handy plastic tray. Sizes from 2.5mm to 13mm supplied diameter. 2:1 Shrink Ratio, UL Approved, Flame Retardant, RoHS compliant.

Temperature Range: -40°C to 135°C

Material: Flame Retardant Polyolefin

Colour: Black, Blue, Brown, Grey, Green/Yellow, White



Code	Internal Diameter		Box Quantity	Heatshrink Length	Kit Contents
	Max Before Shrink	Min After Shrink			
RMK1	2.5	1.25	20	100	4 x Black, Blue, Brown, Grey, Green/Yellow
	3.0	1.5	15	100	3 x Black, Brown, Grey, Green/Yellow 6x Blue
	5.0	2.5	10	100	2 x Black, Blue, Brown, Grey, Green/Yellow
	6.0	3.0	8	100	2 x Black, Blue, Brown, Grey
	10.0	5.0	10	100	2 x Black, Blue, Brown, Grey, White
	13.0	6.5	10	100	2 x Black, Blue, Brown, Grey, White

Heatshrink Mini Kits RMK2

Our adhesive lined heatshrink kit contains 35 x 100mm pieces, it is designed to protect electrical and mechanical components against moisture and water. All supplied in a handy plastic tray. Sizes from 3.0mm to 19mm supplied diameter. 3:1 Shrink Ratio, RoHS compliant.

Temperature Range: -55°C to 110°C

Material: Flame Retardant Polyolefin

Colour: Black or Red



Code	Internal Diameter		Quantity	Heatshrink Length	Kit Contents
	Max Before Shrink	Min After Shrink			
RMK2	3.0	1.0	18	100	14 x Black 4 x Red
	6.0	2.0	9	100	6 x Black 3 x Red
	9.0	3.0	4	100	3 x Black 1 x Red
	12.0	4.0	2	100	1 x Black, 1 x Red
	19.0	6.0	2	100	1 x Black, 1 x Red

Hot Air Heat Guns

The Iroda flame less heat gun has a piezoelectric self-starting ignition system. Powered by the refill cell of a disposable lighter. Windproof flame and waterproof ignition. Handy compact size and easy to use. Uses Butane fuel (not included).

Applications: Compact size, ideal for quick heatshrink applications.

DeWalt Heat Gun. Durable, ergonomic and compact variable cone attachments for greater versatility. Suitable for stripping paint, softening adhesives and automotive applications. Stand incorporated into handle for stationary use.

Applications: Ideal for soldering, de-soldering, heat-shrinking, pipe bending

Code	Description	Dimensions	Heat Temperature	Voltage
HSG1	Mini Heatshrink Gun	115 x 80 x 25	Up to 650°C	N/A
HSG2	DeWalt D26411 Heat Gun	260 x 90 x 25	Variable 50°C to 600°C	230-240V, 50Hz

