

PRE-INSULATED SPADE TERMINALS | Terminals


PRE-INSULATED CRIMP TERMINALS



Fully Insulated Female Spade Terminals

Fully insulated female spade terminals.

Temperature Range: -10°C to 75°C
Material: Tin Plated Electrolytic Copper / Vinyl
Voltage: 300V
Colour: Red, Blue, Yellow




Code	Colour	Range mm ²	ID (A)	Length (L1)	Length (L2)	Width (W)
RFS28FI-5		0.5-1.5	1.7	10.5	19.0	3.2
RFS28FI-8		0.5-1.5	1.7	10.5	19.0	3.2
RFS48FI-5	Red	0.5-1.5	1.7	10.5	19.0	5.0
RFS48FI-8		0.5-1.5	1.7	10.5	19.0	5.0
RFS63FI		0.5-1.5	1.7	10.5	21.8	6.6
BFS48FI-5		1.5-2.5	2.3	10.5	19.0	5.0
BFS48FI-8	Blue	1.5-2.5	2.3	10.5	19.0	5.0
BFS63FI		1.5-2.5	2.3	10.5	22.8	6.6
YFS63FI	Yellow	4.0-6.0	3.4	10.9	23.8	6.6
YFS95FI		4.0-6.0	3.4	10.9	30.0	10.0



Pre-Insulated Piggy Back Spade Terminals

Pre-insulated piggy back spade terminals.

Temperature Range: -10°C to 75°C
Material: Tin Plated Electrolytic Copper / Vinyl
Voltage: 300V
Colour: Red, Blue, Yellow




Code	Colour	Range mm ²	ID (A)	Length (L1)	Length (L2)	Width (W)
RPB63	Red	0.5-1.5	1.7	12.0	21.0	6.7
BPB63	Blue	1.5-2.5	2.3	12.0	21.0	6.7
YPB63	Yellow	4.0-6.0	3.4	11.0	24.5	6.7



Fully Insulated Female Flag Spade Terminals

Fully insulated female flag spade terminals.

Temperature Range: -40°C to 105°C
Material: Tin Plated Electrolytic Copper / Vinyl
Voltage: 300V
Colour: Red, Blue



Code	Colour	Range mm ²	ID (A)	Length (L2)	Width (W)
RFLAG63	Red	0.5-1.5	1.7	16.0	6.6
BFLAG63	Blue	1.5-2.5	2.3	16.0	6.6