

# METALLIC CONDUIT | Flexible Conduit Systems

## FLEXIBLE GALVANISED STEEL CONDUIT

### Flexible Conduit - Galvanised Steel PVC Covered

- Square locked galvanised steel conduit with PVC cover, good mechanical stability and flexibility.


**Temperature Range:** -40°C to 70°C

**Crush Resistance:** 1250N

**IP Rating:** IP54

**Material:** Galvanised Steel to DIN 53210 / PVC Coating

**Standards:** EN 61386.1 / 2005



Code	Conduit Size	Conduit ID	Conduit OD	Coil Length (m)
GALV-PVC-M20/25	20	17.0	21.0	25m
GALV-PVC-M20/50	20	17.0	21.0	50m
GALV-PVC-M25/25	25	20.5	26.0	25m
GALV-PVC-M25/50	25	20.5	26.0	50m
GALV-PVC-M32/25	32	26.5	32.0	25m
GALV-PVC-M40/10	40	34.5	40.0	10m
GALV-PVC-M50/10	50	39.5	46.5	10m
GALV-PVC-M63/10	63	50.5	57.0	10m



### Contractor Packs

Why not get all the basics in 1 pack? With 20, 25 and 32mm conduit in PVC coated galvanised steel, we have it covered. Our SoliFlex Contractor Packs come complete with 10 meters of flexible conduit, 10 straight fixed glands and 10 lock nuts to suit. It's as simple as that.

- Pack consists of 10 meters of PVC coated steel conduit and 10 straight fittings including 10 locknuts.


**Temperature Range:** -40°C to 70°C

**Crush Resistance:** 1250N

**IP Rating:** IP54

**Material:** Galvanised Steel to DIN 53210 / PVC Coating

**Standards:** EN 61386.1 / 2005



Code	Conduit Size	Conduit ID	Conduit OD	Coil (m)
GALV-PVC-CON-M20/10	20	17.0	21.0	10m
GALV-PVC-CON-M25/10	25	20.5	26.0	10m
GALV-PVC-CON-M32/10	32	26.5	32.0	10m



### P Clip Galvanised Steel

**Material:** Galvanised Steel / Elastomer Liner

**Colour:** Black



Code	Colour	Conduit Size
PC12	Black	12
PC16	Black	16
PC20	Black	20
PC25	Black	25
PC32	Black	32
PC40	Black	40
PC50	Black	50



Call the Remora sales team at **01226 352 000**

Challenge us - We find a solution